

# Data Communications, Computer Networks and Open Systems

Fourth Edition

Fred Halsall

Newbridge Professor of Communications Engineering  
University of Wales, Swansea

*C Demartini*

*C Schoute*

*N Huber*



Addison-Wesley Publishing Company

Wokingham, England • Reading, Massachusetts • Menlo Park, California  
New York • Don Mills, Ontario • Amsterdam • Bonn • Sydney • Singapore  
Tokyo • Madrid • San Juan • Milan • Paris • Mexico City • Seoul • Taipei

Apple Inc. v. Rembrandt Wireless Technologies, LP, IPR2020-00034

Page 1 of 14

© 1996 Addison-Wesley Publishers Ltd.  
© 1996 Addison-Wesley Publishing Company Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of the publisher.

The programs in this book have been included for their instructional value. They have been tested with care but are not guaranteed for any particular purpose. The publisher does not offer any warranties or representations, nor does it accept any liabilities with respect to the programs.

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Addison-Wesley has made every attempt to supply trademark information about manufacturers and their products mentioned in this book.

Cover designed by Op den Brouw, Design and Illustration, Reading  
incorporating photograph © D. Redfearn/The Image Bank  
and printed by The Riverside Printing Co. (Reading) Ltd.  
Typeset by CRB Associates, Norwich.

Printed in the United States of America.

First edition published 1985. Reprinted 1986, 1987.  
Second edition published 1988. Reprinted 1988, 1989.  
Third edition published 1992. Reprinted 1992, 1993 (twice), 1994.  
Fourth edition printed 1995.

ISBN 0-201-42293-X

**British Library Cataloguing in Publication Data**

A catalogue record for this book is available from the British Library.

**Library of Congress Cataloging in Publication Data** applied for.

Objectiv

Intende

synchronous, character-oriented/bit-oriented, parity/CRC, etc. – by writing defined bit patterns into selected internal registers. We also referred to these circuits as **universal communication interface circuits**. Normally, a single circuit provides one, two or even four separate (full-duplex) transmission line interface circuits.

The device controlling the operation of the circuit – a microprocessor, for example – first programs the desired operating mode by writing a defined byte (bit pattern) into the **mode register**. The device is then made ready to transmit and/or receive characters/bytes by writing a second byte into a **command register**. The transmit and receive channels are always **double-buffered** which means that the controlling device has a full character (or byte) time to process each character (byte) prior to transmission or after reception, rather than a single bit time.


The names and functions of the most common devices are as follows:

- *Universal asynchronous receiver transmitter (UART)*
  - Start and stop bit insertion and deletion
  - Bit (clock) synchronization
  - Character synchronization
  - Parity bit generation and checking per character (BCC computed by controlling device)
- *Universal synchronous receiver transmitter (USRT)*
  - Low bit rate DPLL clock synchronization
  - Character synchronization
  - Synchronous idle character generation
  - Parity generation and checking per character (BCC computed by controlling device)
- *Universal synchronous/asynchronous receiver transmitter (USART)*
  - Can be programmed to operate as either a UART or a USRT
  - Has all the programmable features of both devices
- *Bit-oriented protocol circuits (BOPs)*
  - Opening and closing flag insertion and deletion
  - Zero bit insertion and deletion
  - CRC generation and checking
  - Idle pattern generation
- *Universal communications control circuits*
  - Can be programmed to operate either as a UART, a USRT, or a BOP
  - Has all the programmable features of each circuit

### 3.7 Communications control devices

In many data communication applications, a common requirement is to have a distributed community of terminals – personal computers, for example – that all require to access a central computing facility. This facility could operate a central

**Figure 3.29**  
Simple terminal networks: (a) locally distributed; (b) remotely distributed.



**Figure 3.29**  
Simple terminal networks: (a) locally distributed; (b) remotely distributed.


electronic mail service for an enterprise, or house a central database to which the distributed community of terminals requires access.

If all the terminals are situated in different locations, the only solution is to provide a separate communications line for each terminal, as shown in Figure 3.29. In part (a) we assume that the terminals are distributed around a single establishment, whereas in part (b) we assume that they are each located in different establishments. In the latter case, it is likely that modems will be required operating over switched connections or leased lines, depending on the amount of data to be transferred and the frequency of calls. In the case of switched connections, the terminals will normally have autodial facilities associated with the communications interface.

For applications in which a number of terminals are located together, we can use a device known as a **multiplexer (MUX)** to minimize the number of transmission lines required. Such devices are used with a single transmission line that operates at a higher bit rate than the individual user terminal rates. As Figure 3.30 shows, we normally use a similar multiplexer at each end of the link. In this way the presence of the multiplexers is transparent to both the terminals and the central computer.

There are two types of multiplexer: **time-division multiplexers** and **statistical multiplexers**. A time-division multiplexer assigns each terminal a dedicated

Rembrandt Wireless  
Ex. 2003



**Figure 3.30**  
Multiplexer-based  
network schematic.

portion of the transmission capacity of the shared line. A statistical multiplexer allocates transmission capacity on an on-demand or statistical basis.

### 3.7.1 Time-division multiplexer

A typical time-division multiplexer application is shown in Figure 3.31(a). The terminals located in each establishment associated with an enterprise all require access to the central computer. We assume that each site has a large number of terminals that generate sufficient intersite traffic to justify high bit rate leased circuits being used to link the various sites to the central site. Typically, these are 64 kbps or higher, depending on the number of terminals.

Figure 3.31(b) shows the internal architecture of each MUX. Typically, each terminal operates in an asynchronous transmission mode and is connected to a UART. The controlling microprocessor within the MUX controls the transfer of characters between the UARTs and the high-speed link interface circuit. As the latter normally operates in a character-oriented synchronous transmission mode it will comprise a USRT.

To ensure that the presence of the MUXs is transparent to the terminals/computer, the transmission capacity associated with the high bit rate circuit is divided in such a way that the UARTs in the terminal and computer ports can operate at their programmed rate. This is achieved by a technique known as **rate adaption** which involves breaking the available link capacity into a number of frames as shown in Figure 3.31(c).

Each frame comprises  $N$  bytes such that the bit rate associated with a single byte position in each frame forms a suitable basic multiplexing rate. The bit rates associated with each terminal are then derived by using multiple bytes per frame. However, not all the bits in each byte are used for user data. The first bit in each byte is used for framing; a fixed repetitive bit pattern is sent in this bit position of

**Figure 3.31**  
Time-division  
multiplexer principles:  
(a) application;  
(b) MUX schematic;  
(c) rate adaption.



# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.