

---

# Electric Hybrid Drive Systems for Passenger Cars and Taxis

**A. Kalberlah**  
Volkswagen AG  
Wolfsburg, Germany

**S. A. E.  
LIBRARY**  
2-26-91

Reprinted from SP-862—  
Electric Vehicle Design and Development

BMW v. Paice, IPR2020-00994  
BMW1091  
Page 1 of 12

International Congress and Exposition  
Detroit, Michigan  
February 25-March 1, 1991

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space®  
**INTERNATIONAL**



No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

ISSN 0148-7191  
Copyright 1991 Society of Automotive Engineers, Inc.

BMW v. Paice, IPR2020-00994  
BMW1091  
Page 2 of 12

Positions and opinions advanced in this paper are those of the author(s) and not necessarily those of SAE. The author is solely responsible for the content of the paper. A process is available by which discussions

Persons wishing to submit papers to be considered for presentation or publication through SAE should send the manuscript or a 300 word abstract of a proposed manuscript to: Secretary, Engineering Activity Board

# Electric Hybrid Drive Systems for Passenger Cars and Taxis

A. Kalberlah  
Volkswagen AG  
Wolfsburg, Germany

## Abstract

Various hybrid drive configurations are described and their advantages and disadvantages for application in passenger cars are discussed; specifically, these are the series hybrid, the parallel hybrid, hybrid drives with added torque and speed, single and two-shaft hybrids.

The Volkswagen and AUDI group has developed different vehicles with hybrid drive for various applications. These vehicles are described and test results are presented on their energy consumption, emissions and driving performance. In conclusion, some considerations are pursued concerning their chances on the market in different scenarios.

## 1. INTRODUCTION

A hybrid drive, comprising both electric drive and internal combustion engine, can, if suitably designed, combine the advantages of the conventional vehicle drive system (large cruising range, good performance) with those of a purely electric drive (low noise and exhaust emissions, conservation of petroleum resources).

Vehicles equipped with such drive systems are thus far more flexible than electric vehicles; they are often just as versatile as vehicles with an internal combustion engine and consequently are not confined from the outset to the "second car" market.

Hybrid drives thus have far more extensive potential applications than electric drives; higher production rates could in principal therefore be achieved, leading to low manu-

Surprisingly, there is a wealth of possibilities for realizing such hybrid drives. Some of these possibilities are outlined below and the advantages and disadvantages of these different designs are investigated by considering vehicles already manufactured.

## 2. SYSTEM ANALYSIS OF HYBRID DRIVES

2.1 SERIES HYBRID DRIVE - Taking the purely electric drive as a starting point, it is simple to conceive of a hybrid drive: the batteries of the electric vehicle are recharged when driving as required via generator driven by an internal combustion engine. This is not only simple in concept, but also in practice; several VW Electric Transporters, fitted with a suitable motor/generator assembly in the loading area, have been transferred from Wolfsburg to Essen. In actual fact, not only improvised vehicle drives have been built according to this principle, but also real drives, e.g. by Daimler Benz (1)\* for a city bus.


The main advantage of the series hybrid:

It is possible to operate the internal combustion engine at a fixed operating point within its engine-speed/torque map. This point can be selected so that the engine functions with the greatest efficiency or produces particularly low emissions.

Nevertheless, the efficiency of the entire drive is not satisfactory. As the structure of this so-called series drive in Fig. 1 clearly shows, the 3 components V (internal combustion engine), G (generator) and E (electric motor) are arranged in series: the mechanical energy generated by the petrol

\*Numbers in parentheses designate references

engine is converted into electrical energy by the generator and this is again converted back into mechanical energy in the electric motor. Each process of conversion is afflicted with losses resulting in relatively bad efficiency. This is also confirmed by test results from a fleet of hybrid buses which were operated in Esslingen.



**Fig 1 Structure of the series hybrid drive**

A further disadvantage of this series hybrid drive is its heavy weight.

If power  $P_{max}$  is required at the drive axle e.g. for the maximum speed, the electric motor must be designed to produce this power  $P_{max}$ . If the driver wishes to drive long distances at this maximum speed, the power, which the battery could contribute, can be disregarded so that both, the generator and the internal combustion engine must be designed for the power  $P_{max}$  (because of the conversion losses in the electric motor and the generator, the power to be employed by the internal combustion engine would be even greater). A total power of over  $3 P_{max}$  is required to drive at  $P_{max}$ . That makes this drive difficult to use in a universal vehicle (e.g. passenger cars) and expensive - particularly due to the two electric components.


For a vehicle, which only travels in the city, e.g. a delivery van or city bus, it may suffice, if the internal combustion engine and generator of the series hybrid are designed for average performance, since the battery could then provide for the power peaks. If this average performance is set at  $1/2 P_{max}$ , it can be seen that, even in these urban vehicles, engines would have to be installed with power of more than  $2 P_{max}$ .

Only if the combustion engine and the generator are very small compared to the electric motor - e.g. like in a range extender for electric vehicles (2), the series hybrid structure may be acceptable because additional weight, volumes and costs are small.

The problem of energy efficiency is neglectable in this case because most of the driving energy comes as electricity from the public network over the battery and the electric motor to the wheels and only a small amount comes out of the fuel tank over the IC-engine, the generator and the electric motor.

Another situation would be given, if the efficiency of the generator and the electric motor together are as good as the efficiency of the conventional gearbox. In this case, not only a series hybrid could make sense, but even a generator-motor-set instead of the mechanical gearbox. Some companies hope to be able to do this by using high speed synchronous generators and motors with new permanent magnets having a very high magnetic energy density (3).

But regarding Fig 2 showing that the efficiency of a mechanical gearbox is in a wide range over 90 %, it seems to be a long way to the "electrical gearbox".



**Fig. 2 Efficiency of a typical mechanical gearbox over the torque of the input shaft for different rotation numbers.**

2.2 PARALLEL HYBRID DRIVES - Fig. 3 illustrates a parallel hybrid drive. Here, the internal combustion engine V and the electric motor E are not arranged in series (considering their power flow) but in parallel. The power provided by the two motors could be added to the vehicle drive. In this way, the power  $P_{max}$  required to drive a city vehicle, could be provided by designing e.g. both the internal combustion engine and the electric motor to give the power  $1/2 P_{max}$  each. (For a series hybrid under the same conditions, at least  $2 P_{max}$  would have to be installed.)




Fig. 3 Structure of a parallel hybrid drive

Whilst the series hybrid requires 2 electric machines, only one is present in the parallel hybrid. Nevertheless, even with the parallel hybrid, neither regenerative braking nor recharging the battery when driving should be disregarded, since the electric motor E can also function as a generator, e.g. if the total power of the internal combustion engine is not required to drive the axles.

Turning to a parallel hybrid for a universal vehicle requires the drive power  $P_{max}$  for longer periods, e.g. for long distances on the motorway. In this case, the power of the internal combustion engine must be  $P_{max}$ . The power of the electric motor could be selected from this completely independently. If  $P_{max}$  is selected for this too, since the series hybrid - if the battery power permits - can drive purely electrically at  $P_{max}$ , a total drive power of only  $2 P_{max}$  needs to be installed. For a series hybrid under the same conditions, this would require more than  $3 P_{max}$ .

In reality it is more sensible to select a much lower value for the power of the electric drive in such a parallel hybrid; i.e. a level which permits purely electric inner-city driving with acceptable performance. This is another point in favour of the parallel hybrid. The advantages of the parallel hybrid

follows:

- Improved efficiency and thereby lower fuel consumption in the internal combustion engine, since its mechanical energy is directly passed on to the drive axle. (Only if the battery is charged during driving - which should be avoided for reasons of conserving energy - is the same unfavourable efficiency chain present as in the series hybrid.)
- The generator is no longer required
- The weight is lower
- Costs are lower

### 2.3 STRUCTURES OF PARALLEL HYBRID DRIVES -

Parallel hybrid drives can be realized in the most diverse forms, since the two mechanical power plants can be combined in various ways.

The version already discussed is illustrated at the far left of Fig. 4. Because of its two parallel-running drive shafts, we like to call this the two-shaft configuration.

In the next structure both drive units are arranged around a single shaft. As in the two-shaft configuration, the torques are added (or, in generator operation, subtracted), and this provides a free choice, within certain limits, in determining the extent to which the two units contribute to the total drive torque. This provides e.g. the opportunity to compensate for rapid changes in the desired torque with the electric motor torque and to permit only very slow changes in the throttle-valve setting in the internal combustion engine. This sluggishness in the throttle-valve has the effect of reducing exhaust emissions. However, the engine speeds are determined by the gearbox transmission. There is no opportunity for selection here.

The situation is reversed in the third structure illustrated in Fig. 4. Here, the power combination is performed by adding together the speeds of rotation of both drives in a differential gearbox positioned between the two units. There is, therefore, a certain freedom in dividing the speed between the two units, but the torques are fixed by the desired drive torques. In consequence, it is impossible to retard the throttle valve. A further disadvantage arises from the fact that the electric motor torque, on the one hand, and the petrol engine torque, on the other hand, must always be equal, although the torque-speed maps of both units are vastly different. Therefore, it is impossible to utilize e.g. the high torque of the electric motor at low speeds of revolution, which

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.