

## CERTIFICATION OF TRANSLATION ACCURACY

I, Michael Fletcher, declare:

1. I am well versed in both the Japanese and English languages and have over 13 years of experience translating Japanese technical documents into English.
2. The following translation of this Japanese patent document to English is accurate and complete to the best of my knowledge.

I declare under penalty of perjury under the laws of the United States of America that the foregoing is true and accurate.

Executed this 31<sup>st</sup> day of October 2017, at Parowan, UT



Michael Fletcher



(51) International Patent Classification 6 H05B 33/00	A1	(11) International Application No. WO96/25020 (43) International Publication Date August 15, 1996
(21) International Application No. PCT/JP96/00233 (22) International Application Date February 5, 1996  (30) Priority Rights Data Application No. 7/41267 February 6, 1995 JP Application No. 7/49089 February 14, 1995 JP Application No. 7/299111 October 24, 1995 JP		(81) Designated Countries CN, US, European Patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Attached Publication International Search Report
<p>(71) Applicant (all designated countries except the US) IDEMITSU KOSAN CO., LTD. [JP/JP] 3-1-1 Marunoushi, Chiyoda-ku, Tokyo (JP)</p> <p>(72) Inventor; Same</p> <p>(75) Inventor/Applicant (Only for US) EIDA, Mitsuru [JP/JP] MATSUURA, Masahide [JP/JP] TOKAILIN, Hiroshi [JP/JP] c/o Idemitsu Kosan Co., Ltd. #1280 Kamiizumi Sodegaura City, Chiba (JP)</p> <p>(74) Agent Patent Attorney WATANABE, Kihei et al. c/o Diamont Bldg. 8F 1-5 Kanda Sudacho Chiyoda-ku, Tokyo (JP)</p>		
(54) Title: MULTI-COLOR LIGHT EMISSION APPARATUS AND METHOD FOR PRODUCTION THEREOF		
<p>(57) Abstract:</p> <p>This invention provides a multi-color light emission apparatus wherein a transparent glass substrate (4) is disposed between an organic EL device (1) and a fluorescent layer (3) in such a manner as to arrange the fluorescent layer (3) with a gap with the organic EL device (1), and the organic EL device (1) is sealed by seal means (5) between the transparent glass substrate (4) and a support substrate (2). The invention provides also a multi-color light emission apparatus wherein a transparent insulating inorganic oxide layer (12) having a thickness of 0.01 to 200 μm is interposed between the fluorescent layer (3) and the organic EL device (1). In this way, light emission life and angle-of-field characteristics can be improved.</p>		

(57) Abstract:

(57) Abstract

The present invention provides a multi-color light emission apparatus wherein a transparent glass substrate 4 is disposed between an organic EL element 1 and a fluorescent layer 3 in such a manner as to arrange the fluorescent layer 3 with a gap with the organic EL element 1 and the organic EL element 1 is sealed by sealing means 5 between the transparent glass substrate 4 and a support substrate 2. The invention provides also a multi-color light emission apparatus wherein a transparent insulating inorganic oxide layer 12 having a thickness of 0.01 to 200  $\mu\text{m}$  is disposed between the fluorescent layer 3 and the organic EL element 1.

For information purposes only

Codes used to stipulate PCT member nations on the first page of the pamphlet for international publications released based on PCT

AL	Albania	DE	Germany	LI	Liechtenstein	PL	Poland
AM	Armenia	DK	Denmark	LC	Saint Lucia	PT	Portugal
AT	Austria	EE	Estonia	LK	Sri Lanka	RO	Romania
AU	Australia	ES	Spain	LR	Liberia	RU	Russia
AZ	Azerbaijan	FI	Finland	LS	Lesotho	SD	Sudan
BA	Bosnia and Herzegovina	FR	France	LT	Lithuania	SE	Sweden
BB	Barbados	GA	Gabon	LU	Luxemburg	SG	Singapore
BE	Belgium	GB	The United Kingdom of Great Britain and Northern Ireland	LV	Latvia	SI	Slovenia
BF	Burkina Faso	GE	Georgia	MC	Monaco	SK	Slovakia
BG	Bulgaria	GN	Guinea	MD	Republic of Moldova	SN	Senegal
BJ	Benin	GR	Greece	MG	Madagascar	SZ	Swaziland
BR	Brazil	HU	Hungary	MK	North Macedonia (former Yugoslavia)	TD	Chad
BY	Belarus	IE	Ireland	ML	Mali	TG	Togo
CA	Canada	IL	Israel	MN	Mongolia	TJ	Tajikistan
CF	Central African Republic	IS	Iceland	MR	Mauritania	TM	Turkmenistan
CG	Congo	IT	Italy	MW	Malawi	TR	Turkey
CH	Switzerland	JP	Japan	MX	Mexico	TT	Trinidad and Tobago
CI	Cote d'Ivoire	KE	Kenya	NE	Niger	UA	Ukraine
CM	Cameroon	KG	Kyrgyzstan	NL	Netherlands	UG	Uganda
CN	China	KP	Democratic People's Republic of Korea	NO	Norway	US	United States of America
CU	Cuba	KR	South Korea	NZ	New Zealand	UZ	Uzbekistan
CZ	Czech Republic	KZ	Kazakhstan			VN	Vietnam

## SPECIFICATION

Multi-color light emission apparatus and a method for producing thereof.

## FIELD OF THE INVENTION

This invention relates to a multi-color light emission apparatus and a method for producing thereof. More specifically, this invention relates to a multi-color light emission apparatus suitable for use in multi-color or full-color thin-type displays and a method for producing the multi-color light emission apparatus.

## BACKGROUND TECHNOLOGY

An electroluminescence element (hereinafter called "EL element") is characterized in exhibiting high visibility due to self-emission and in having excellent impact resistance because of being completely solid. At present, various EL elements using an inorganic or an organic compound as the emitting layer have been proposed and attempts have been made to put them to practical use. One of the EL elements that has been put to practical use is applied as a multi-color light emission apparatus.

Such a multi-color light emission apparatus includes an apparatus produced by arranging a color filter of three primary colors (red, green, and blue) with a white-light emitting inorganic EL element and an apparatus produced by patterning inorganic EL elements of three primary colors in order to position the EL elements of three primary colors separately on the same plane and thereby emit light (Semicond. Sci. Technol. 6 (1991) 305-323). However, there is the problem that the light emission efficiency for each color is limited to 33% of the white light at most if the white color is decomposed by the color filter of three primary colors. Further, elements that can efficiently emit white light have still not been attained at present.

On the other hand, a photolithography process is used for patterning EL elements. However, it is known that the efficiency and stability of EL elements are greatly reduced in this type of wet process.

It is common knowledge that of EL elements, organic EL elements are promising as high luminance and efficient light emitting devices. In particular, because the light emitting layer is

1 an organic layer, it is highly probable that various color emissions are produced by the  
2 molecular design of organic compounds. Such an organic EL element is expected to be one  
3 device which can be used in practice in a multi-color light emission apparatus.  
4

5 However, these organic EL elements have the drawback that chemical factors such as  
6 external water vapor, oxygen, organic compound gas, and the like cause deterioration such  
7 as reduction in luminance accompanied by the occurrence of dark spots and the like and  
8 these devices are damaged relatively readily from physical (mechanical) factors such as  
9 heat, impact, or the like since the element structure is composed of a laminate of low  
10 molecular organic compounds.  
11

12 Therefore, the method for separately disposing each of the organic EL elements, which  
13 emit light in three primary colors (RGB), on the same plane was difficult to use in a wet  
14 process or a process including heat treatment such as a photolithography process.  
15

16 In order to solve such a problem, disclosed is a color EL display apparatus (see Japanese  
17 Patent Application S65-40888). This apparatus is, as shown in FIG. 8, characterized in that  
18 an EL emitting layer 1b sandwiched between a lower electrode 1c and a light transmitting  
19 upper electrode is provided on a substrate 2, the EL light which is output via the light  
20 transmitting electrode 1a is externally output from a transmitting substrate 8 via a color filter 9  
21 provided on the transmitting substrate 8 with the color filter 9 facing the transmitting electrode  
22 1a (Japanese Unexamined Patent Application S64-40888).  
23

24 This apparatus has, however, the disadvantage that the luminance of the light of each color  
25 is reduced to one third of the EL light by the color filter. Also, because the EL element faces  
26 the color filter, the light emission life span of the EL element is invariably reduced by water  
27 vapor, oxygen, gas from organic monomers, low molecular components, and the like  
28 generated by the color filter.  
29

30 To solve these problems, recently disclosed is a technique in which a fluorescent layer that  
31 absorbs light emitted from an organic EL element and emits visible fluorescent light is  
32 installed in the position (laminated or in parallel) corresponding to the emitting part of an

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.