

MICHAEL M. DE ANGELI, P.C.
 ATTORNEY AT LAW
 SUITE 330
 1901 RESEARCH BOULEVARD
 ROCKVILLE, MARYLAND 20850
 (301) 217-9585

FAX: (301) 217-9345
 E-MAIL: MDEA@EROLS.COM

JCB41 U.S. PRO
 60/10095
 09/14/98

09/14/98



J-535 U.S. PTO
 REGISTERED PATENT
 ATTORNEY
 ADMITTED TO BARS
 OF PA & MD

This is a request for filing a PROVISIONAL APPLICATION >FOR PATENT< under 37 CFR 1.53 (b)(2).

Docket Number		PAICE981		Type a plus sign (+) inside this box ->	+
INVENTOR(s)/APPLICANT(s)					
LAST NAME	FIRST NAME	MIDDLE >NAME/< INITIAL	RESIDENCE (CITY AND EITHER STATE OR FOREIGN COUNTRY)		
Severinsky	Alex	J.	Washington, D.C.		
TITLE OF THE INVENTION (250 characters max)					
IMPROVEMENTS IN HYBRID VEHICLES					
CORRESPONDENCE ADDRESS >(including country if not United States)<					
Michael de Angeli 1901 Research Boulevard, Suite 330 Rockville MD 20850					
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/>	Specification	Number of Pages	19	<input type="checkbox"/>	Small Entity Statement
<input checked="" type="checkbox"/>	Drawing(s)	Number of Sheets	4	<input type="checkbox"/>	Other (specify)
METHOD OF PAYMENT (check one)					
<input checked="" type="checkbox"/>	A check or money order is enclosed to cover the Provisional filing fees			FROVISIONAL FILING FEE AMOUNT (\$)	\$150.00
<input type="checkbox"/>	The Commissioner is hereby authorized to charge filing fees and credit Deposit Account Number: _____				

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

No.
 Yes, the name of the U.S. Government agency and the Government contract number are: _____

Respectfully submitted,

SIGNATURE

Date 9/11/98

TYPED or PRINTED NAME

Michael de Angeli

REGISTRATION NO.
 (if appropriate)

27,869

Additional inventors are being named on separately numbered sheets attached hereto

ELECTRONIC SIGNATURE

PROVISIONAL PATENT APPLICATION
of
ALEX J. SEVERINSKY
for
IMPROVEMENTS IN HYBRID VEHICLES

Field of the Invention

5
10
15
20
25
This application relates to improvements in hybrid vehicles, that is, vehicles in which both an internal combustion engine and one or more electric motors are provided to supply torque to the driving wheels of the vehicle.

Background of the Invention

10
15
20
25
This application discloses a number of improvements over and enhancements to the hybrid vehicles disclosed in the inventor's U.S. patent 5,343,970 (the "'970 patent"), which is incorporated herein by this reference. Where differences are not mentioned, it is to be understood that the specifics of the vehicle design shown in the '970 patent are applicable to the vehicles shown herein as well. Discussion of the '970 patent herein is not to be construed to limit the scope of its claims.

20
25
Generally speaking, the '970 patent discloses hybrid vehicles wherein a controllable torque transfer unit is provided capable of transferring torque between an internal combustion engine, an electric motor, and the drive wheels of the vehicle. The direction of torque transfer is controlled by a microprocessor responsive to the mode of operation of the vehicle, to provide highly efficient operation over a wide variety of operating conditions, and while providing good performance.

25
The flow of energy - either electrical energy stored in a substantial battery bank, or chemical energy stored as combustible fuel - is similarly controlled by the microprocessor. For example,

in low-speed city driving, the electric motor provides all torque needed responsive to energy flowing from the battery. In high-speed highway driving, where the internal-combustion engine can be operated efficiently, it typically provides all torque; additional torque may be provided by the electric motor as needed for acceleration, hill-climbing, or passing. The electric motor is also used to start the internal-combustion engine, and can be operated as a generator by appropriate connection of its windings by a solid-state, microprocessor-controlled inverter. For example, when the state of charge of the battery bank is relatively depleted, e.g., after a lengthy period of battery-only operation in city traffic, the internal combustion engine is started and drives the motor at between 50 and 100% of its maximum torque output, for efficient charging of the battery bank. Similarly, during braking or hill descent, the kinetic energy of the vehicle can be turned into stored electrical energy by regenerative braking.

The hybrid drive train shown in the '970 patent has many aspects and advantages with respect to the prior art which are retained by the present invention. For example, the electric drive motor is selected to be of relatively high power, specifically, equal to or greater than that of the internal combustion engine, and to have high torque output characteristics at low speeds; this allows the conventional multi-speed vehicle transmission to be eliminated. As compared to the prior art, the battery bank, motor/generator, and associated power circuitry are operated at relatively high voltage and relatively low current, reducing losses due to resistive heating and simplifying component selection and connection.

Objects of the Invention

It is an object of the present invention to provide further improvements over the hybrid vehicle shown in the '970 patent.

It is a more specific object of the present invention to provide a hybrid drive system for vehicles that does not require the controllable torque-transfer unit shown in the '970 patent,

while providing the functional advantages of the hybrid vehicle shown in the '970 patent.

Other aspects of and improvements provided by the present invention will appear below.

5

Summary of the Invention

10

15

20

25

30

According to the present invention, the controllable torque-transfer unit shown in the '970 patent is eliminated by replacing the single electric motor shown therein by two separate motors, both operable as generators when appropriate, connected by a functionally-conventional clutch or mechanical interlock operated by the microprocessor responsive to the vehicle's mode of operation and to input commands provided by the operator of the vehicle. As in the '970 patent, an internal combustion engine is provided, sized to provide sufficient torque for the maximum cruising speed desired, and is used for battery charging as needed. A relatively high-powered "traction" motor is connected directly to the output shaft of the vehicle; the traction motor provides torque to propel the vehicle in low-speed situations, and provides additional torque when required, e.g., for acceleration, passing, or hill-climbing during high-speed driving. A relatively low-powered starting motor is also provided, and can be used to provide torque propelling the vehicle when needed. This second motor is connected directly to the internal combustion engine for starting the engine. Unlike a conventional starter motor, which rotates an internal combustion engine at low speed for starting, necessitating provision of a rich fuel/air mixture for starting, the starter motor according to the invention spins the engine at relatively high speeds for starting; this allows starting the engine with a near-stoichiometric mixture, significantly reducing undesirable emissions and improving fuel economy at start-up.

35

As noted, the two motors are separated by a functionally-conventional clutch, that is, a clutch which either joins the two motors together for rotation at the same speed, or separates them completely. As the motor shafts can be controlled to rotate at

essentially the same speed when the clutch is engaged, the clutch need not allow for slip therebetween. Accordingly, a friction clutch, as normally provided for road vehicles, is not required, and a less-expensive simple mechanical interlock can alternatively
5 be employed. Engagement of the clutch is controlled by the microprocessor, e.g., by a hydraulic actuator, responsive to the state of operation of the vehicle and the current operator input.

For example, during low-speed operation, the clutch will be disengaged, so that the traction motor is disconnected from the
10 engine; the vehicle is then operated as a simple electric car, i.e., power is drawn from the battery bank and supplied to the traction motor. If the batteries become depleted, the starter motor is used to start the internal combustion engine, which is then runs at relatively high torque output (e.g., between about 50
15 - 100% of its maximum torque), for efficient use of fuel, and the starting motor is operated as a high-output generator to recharge the battery bank. If the operator calls for more power than available from the traction motor alone, e.g., in accelerating onto a highway, the starter motor starts the internal combustion engine,
20 and the clutch is engaged, so that the engine and starter motor can provide additional torque. The engine is sized so that it provides sufficient power to maintain a suitable highway cruising speed while being operated in a torque range providing good fuel efficiency; if additional power is then needed, e.g., for hill-climbing or passing, the traction and/or starter motors can be
25 engaged as needed. Both motors can be operated as generators, e.g., to transform the vehicle's kinetic energy into electrical power during descent or deceleration.

In each of these aspects of the operation of the vehicle, and
30 as in the '970 patent, the operator of the vehicle need not consider the hybrid nature of the vehicle during its operation, but simply provides control inputs by operation of the accelerator and brake pedals. The microprocessor determines the proper state of operation of the vehicle based on these and other inputs and
35 controls the various components of the hybrid drive train

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.