

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	IEEE 802.16m Requirements	
Date Submitted	<b>2007-01-12</b>	
Source(s)	Wookbong Lee, Binchul Ihm, Ronny (Yong-Ho) Kim, LG Electronic Inc. LG R&D Complex, 533 Hogye-1dong, Dongan-gu, Anyang, 431-749, Korea	Voice: +82-31-450-1879 Fax: +82-31-450-7912 <a href="mailto:ronnykim@lge.com">[mailto:ronnykim@lge.com]</a>
Re:	Call for Initial Input	
Abstract	This contribution introduces requirements to 802.16m for discussion.	
Purpose	This document introduces a 802.16m requirements	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# Requirements for 802.16m

Wookbong Lee, Binchul Ihm, Ronny (Yong-Ho) Kim  
LG Electronics, Inc.

## 1. Introduction

IEEE 802.16m amends the IEEE 802.16 WirelessMAN-OFDMA specification to provide an advanced air interface for operation in licensed bands. It will meet the cellular layer requirements of IMT-Advanced next generation mobile networks [1]. It will be designed to provide significantly improved performance compared to other high rate broadband cellular network systems. For the next generation mobile networks, it is important to consider increasing peak, sustained data rates, corresponding spectral efficiencies, system capacity and cell coverage as well as decreasing latency and providing Quality-of-Service while carefully considering overall system complexity.

### 1.1 System performance of systems in legacy spectrum

The following table shows system performance of current system or candidate for IMT-2000.

	Carrier frequency	Bandwidth	Duplex	Peak data rate		Spectral efficiency	
				DL	UL	DL	UL
3GPP WCDMA (HSPA)	2GHz	5 MHz	FDD	14Mbps @ 5MHz	5.8Mbps @ 5MHz	0.8bps/Hz	0.3bps/Hz
3GPP2 CDMA2000 (1xEVDO-RevB)	2GHz	1.25MHz (15 channel/ max 5MHz)	FDD	3.1Mbps @ 1.25MHz	1.8Mbps @ 1.25MHz	1bps/Hz	0.3bps/Hz
IEEE 802.16 WiMAX [2]	2.5GHz	5, 7, 8.75, 10 MHz	TDD	46Mbps* / 32Mbps** @ 10MHz	8Mbps* /14Mbps** @ 10MHz	1.9bps/Hz *	0.8bps/Hz *

Table 1. system performance for IMT-2000, \* : DL/UL = 3, \*\* : DL/UL = 1, all for 2x2 MIMO or CSM

Table 2 shows system requirements for ongoing projects for beyond IMT-2000 broadband wireless communication systems.

	Bandwidth h (MHz)	Duplex	Peak data rate		Spectral efficiency		Mobility support
			DL	UL	DL	UL	
3GPP LTE [3]	[1.25],[1.6], 2.5,5,10, 15,20	TDD/ FDD	100Mbps @ 20MHz	50Mbps @ 20MHz	3~4 times Better than WCDMA	2~3 times Better than WCDMA	~350km/h
3GPP2 UMB[4]	~20(in 1.25MHz block)	FDD	500Mbps @ 20MHz	150Mbps @ 20MHz	Outdoor high speed user 3bps/Hz/Sector	Outdoor high speed user 1bps/Hz/Sector	~350km/h
IEEE 802.20 [5]	1.25,5, 10,15,20	FDD	18Mbps @ 5MHz	9Mbps @ 5MHz	3km/h	3km/h	~250km/h
	2.5,5,10, 20,30,40	TDD			2bps/Hz/Sector	1bps/Hz/Sector	
					120km/h	120km/h	
					1.5bps/Hz/Sector	0.75bps/Hz/Sector	

Table 2. system requirement for beyond IMT-2000

## 2. 802.16m requirements

Since IEEE 802.16m shall meet the cellular layer requirements of IMT-Advanced next generation mobile networks, it is important to understand what kinds of features and technologies are required for the IMT-Advanced.

### 2.1 Key features of IMT-Advanced

As identified in various documents including ITU-R M.1645, IMT-Advanced can be as following:

- High degree of commonality of design worldwide
- Compatibility of services within IMT-Advanced and with the fixed networks
- High quality
- Small terminal suitable for worldwide use
- Worldwide roaming capability
- Capability for multimedia applications within a wide range of services and terminals

Systems beyond IMT-2000, for which there may be a need for a new wireless access technology to be developed around the year 2010, capable of supporting high data rates with high mobility. High mobility here covers high speed on highways or fast trains (60km/h to 250km/h, or more.) It is predicted that potential new radio interfaces will need to support data rates of up to approximately 100Mbps for high mobility such as mobile access and up to approximately 1Gbps for low mobility such as nomadic/local wireless access, by around the year 2010. [6]

## 2.2 Key technologies of IMT-Advanced

Key technologies of IMT-Advanced can be listed as below [6]:

1. System related technologies
  - Voice over IP (VoIP)
  - Optimization of IP,
  - Fault-tolerant network architecture
  - Mobile platform technology
  - Security and privacy
  - Cryptography
  - Authentication and mobile electronic commerce
  - Billing
  - Intelligent data filtering
2. Access network and radio interface
  - Modulation and coding schemes
  - Multiple access schemes
  - Adaptive radio interface
  - New antenna concepts and technologies
  - Handover between different radio interfaces (vertical and horizontal)
  - Dynamic QoS control
3. Utilization of spectrum
  - Multiple Input Multiple Output (MIMO)
  - Adaptive antennas
  - Adaptive dynamic channel assignment
  - Spectrum sharing

## 2.3 802.16m Requirements

### 2.3.1 General Requirements

- IEEE 802.16m architecture shall be flexible to support required services from ITU-R.
- IEEE 802.16m system shall support different cell sizes which are expected for cellular layer systems.
- IEEE 802.16m system shall provide seamless interworking with legacy radio access systems including legacy 802.16 systems.
- IEEE 802.16m shall provide high spectral efficiency up to 10bps/Hz. In order to provide high spectral efficiency, IEEE 802.16m system shall support key technologies of IMT-Advanced.

- Required QoS for IMT-Advanced shall be provided including end-to-end latency, throughput, and error performance.
- IEEE 802.16m system shall provide powerful and efficient security mechanism to protect network, system, and user.

### 2.3.2 System Requirements

#### 2.3.2.1 Air Interface Requirement

IEEE 802.16m specification shall meet the following performance requirement.

Characteristic		Requirement
Peak Data Rate	Downlink	1Gbps @ Nomadic 100Mbps @ High mobility
	Uplink	TBD
Expected spectral efficiency	Micro cell (DL/UL)	TBD
	Macro cell (DL/UL)	TBD
Bandwidth		Scalable bandwidth including 5, 7, 8.75, 10 MHz
Center frequency		Frequency is expected to be decided in WRC07

Table 3. Proposed air interface requirement for IEEE 802.16m

#### 2.3.2.2 QoS requirements

IMT-Advanced system shall support the MAC level QoS to meet the end user QoS requirements for the various applications. The system should support the following types of services with different data rates, delay, and packet error rates.

- Conversational/Real-time Services
- Streaming Services
- Interactive Services
- Background Services

The system should realize low-delay and highly reliable radio transmission using error control techniques, and enable flexible allocation of radio resources depending on the required QoS.

Minimizing the system latency under various conditions (e.g. handover, re-entry from Idle Mode, and packet transmission) should be required.

Table 4 shows the QoS classes and profiles for the IMT-Advanced system into Conversational, Streaming, Interactive and Background [8]. Table 4 shows an example of parameters. Parameters shall be considered and values shall be decided for 802.16m requirements.

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.