



- (51) **International Patent Classification:**
H04B 17/00 (2006.01) H04W 24/00 (2009.01)
H04L 1/00 (2006.01)
- (21) **International Application Number:**
PCT/CN2012/080560
- (22) **International Filing Date:**
24 August 2012 (24.08.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (71) **Applicant (for all designated States except US):**
PANASONIC CORPORATION [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** WANG, Lilei [CN/CN]; Panasonic Research & Development Center China Co., Ltd., 18th Floor, Zhongguancun Tower, No.27 Zhongguancun Street, Haidian District, Beijing 100080 (CN). XU, Ming [CN/CN]; Panasonic Research & Development Center China Co., Ltd., 18th Floor, Zhongguancun Tower, No.27 Zhongguancun Street, Haidian District,

Beijing 100080 (CN). HOSHINO, Masayuki [JP/JP]; Panasonic Corporation, 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP). NISHIO, Akihiko [JP/JP]; Panasonic Corporation, 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(74) **Agent:** LIU, SHEN & ASSOCIATES; A0601, Huibin Building, No.8 Beichen Dong Street, Chaoyang District, Beijing 100101 (CN).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

[Continued on next page]

(54) **Title:** COMMUNICATION METHOD, BASE STATION AND USER EQUIPMENT




Fig.7

(57) **Abstract:** The present disclosure provides a communication method, base station and user equipment for configuring a parameter table in a wireless communication system including a base station and a user equipment, the communication method comprising: defining at both the base station and the user equipment a parameter table which includes whole entries of a legacy parameter table and extended entries; and transmitting from the base station to the user equipment a bitmap indication which indicates a sub-table selected from the parameter table, wherein the number of the entries in the sub-table is the same as in the legacy parameter table.

WO 2014/029108 A1



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

COMMUNICATION METHOD, BASE STATION AND USER EQUIPMENT

TECHNICAL FIELD

5

The present disclosure relates to parameter table configuration technique in the communication field.

10 BACKGROUND ART

In 3GPP (3rd Generation Partnership Project) Rel.8/9/10 system, Channel Quality Indicator (CQI), one type of channel state information (CSI), is an important communication parameter used for scheduling and link adaptation at eNodeB (eNB). In practice, since UE (user equipment) knows better about the downlink channel based on certain reference signal, like CRS (common reference signal) or CSI-RS (channel state information-reference signal), CQI is calculated and recommended at UE side. Then, CQI is feedback by the UE with a certain index in the CQI table, which includes some combinations of modulation order and coding rate, referring to Table 7.2.3-1 in 3GPP TS 36.213 V10.5.0, which is entirely incorporated hereto by reference.

Fig. 1 shows the CQI table in TS 36.213. It can be seen from Fig. 1 that the standard CQI table, which may also be referred to as a legacy CQI table, includes 16 entries with indices from 0-15, corresponding to modulation schemes such as QPSK, 16QAM and 64QAM. Therefore, 4 bits are necessary to reflect a certain entry when the UE feedbacks a certain wideband CQI to the eNB.

30 As to other CQI types defined according to different feedback modes or transmission modes, such as subband CQI, spatial CQI or UE selected CQI, UE do not directly feedback the entry/index in the same CQI table as shown in Fig. 1. Instead, an implicit mechanism is used to feedback their CQI offset level from the wideband CQI value. For example,

Subband differential CQI offset level = subband CQI index - wideband CQI index.

Fig. 2 shows the subband differential CQI table in TS 36.213. It can be seen
5 that the standard subband differential CQI table, which may also be referred to
as a legacy subband differential CQI table, includes 4 entries with indices from
0 to 3. Therefore, UE needs 2 additional bits to feedback the subband
differential CQI offset level.

10 Also, Modulation Coding Scheme (MCS) is an important communication
parameter in 3GPP Rel.8/9/10 system. MCS refers to which combination of
modulation order and coding rate is used in physical transmission of downlink
and uplink. There is also a table, called MCS table, restricts which combination
of modulation order and transport block size could be used.

15 Fig. 3 shows the MCS table in TS 36.213. It can be seen that the standard
MCS table, which may also be referred to as a legacy MCS table, includes 32
entries with indices from 0-31, corresponding to modulation orders such as 2, 4
and 6. The last three entries with indices 29-31 are used for re-transmission. In
20 3GPP, which MCS is used is informed in Downlink Control Information (DCI).
And 5 bits are necessary for this indication.

SUMMARY OF THE DISCLOSURE

25 With the future introduction of new technologies and new network deployment,
such as 3D beamforming, massive MIMO and dense deployment of small cell
etc., user equipment has more opportunities to maintain high quality wireless
channel link with high SINR, so it is possible and beneficial for the system to
30 support higher modulation orders than current system, like 256QAM or
1024QAM, in order to further improve the spectral efficiency and user
throughput.

Correspondingly, there is a need to configure the parameter table, such as the

CQI table or the MCS table described above, so that more entries corresponding to higher modulation orders and/or coding rates than those in the legacy tables can be indicated. There is also a need to configure the differential CQI table to indicate more CQI offset levels, so that the indication of the differential CQI can be more accurate.

The present disclosure is made in consideration of the above aspects.

According to one aspect of the present disclosure, there is provided a communication method of configuring a parameter table in a wireless communication system including a base station and a user equipment, comprising: defining at both the base station and the user equipment a parameter table which includes whole entries of a legacy parameter table and extended entries; and transmitting from the base station to the user equipment a bitmap indication which indicates a sub-table selected from the parameter table.

According to another aspect of the present disclosure, there is provided a communication method of configuring a parameter table in a wireless communication system including a base station and a user equipment, comprising: defining at both the base station and the user equipment multiple parameter tables which include at least a legacy parameter table and an aggressive parameter table which includes new modulation order related entries or new combinations of modulation order and coding rate; and transmitting from the base station to the user equipment an indication which indicates a parameter table selected from the multiple parameter tables, wherein the number of entries in any one of the multiple parameter tables is the same as in the legacy parameter table to keep signaling overhead unchanged.

According to a further aspect of the present disclosure, there is provided a communication method of configuring a parameter table in a wireless communication system including a base station and a user equipment, comprising: defining at both the base station and the user equipment a parameter table which includes whole entries of a legacy parameter table and extended entries; and transmitting from the base station to the user equipment an indication which indicates one entry of the parameter table, by legacy bits and at least one unused bit jointly.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.