

## Original Message

Message ID	<E186xfO-0006yt-00@wisbech.cl.cam.ac.uk>
Created at:	Wed, Oct 30, 2002 at 6:34 PM (Delivered after 50030275 seconds)
From:	Andrew Warfield <Andrew.Warfield@cl.cam.ac.uk> Using exmh version 2.5+CL 07/13/2001 with nmh-1.0.4
To:	llp@cs.princeton.edu
Subject:	
SPF:	NONE with IP 0.0.0.0 <a href="#">Learn more</a>

[Download Original](#)
[Copy to clipboard](#)

```

Delivered-To: tim.harris@gmail.com
Received: by 10.11.98.45 with SMTP id v45cs17998cwb;
      Mon, 31 May 2004 12:52:04 -0700 (PDT)
Received: by 10.11.120.80 with SMTP id s80mr225116cwc;
      Mon, 31 May 2004 12:52:04 -0700 (PDT)
Return-Path: <tim.harris@cl.cam.ac.uk>
Received: from 128.232.0.15 (HELO mta1.cl.cam.ac.uk)
      by mx.gmail.com with SMTP id p77si638038cwc;
      Mon, 31 May 2004 12:52:03 -0700 (PDT)
Received: from tempest.cl.cam.ac.uk ([128.232.32.126]
      hello=cl.cam.ac.uk ident=[+XyOQTlPYqkf7q531czcc99LMedmd2KE]) by
      mta1.cl.cam.ac.uk with esmtp (Exim 3.092 #1) id 1BUspG-0006YK-00
      for tim.harris@gmail.com; Mon, 31 May 2004 20:52:02 +0100
Received: from rhone.cl.cam.ac.uk ([128.232.8.183]
      hello=cl.cam.ac.uk ident=[PX+kB1qx13UVZJrWdkahyEZIYyWTt1IF]) by
      wisbech.cl.cam.ac.uk with esmtp (Exim 3.092 #1) id 186xfO-0006yt-
      00; Wed, 30 Oct 2002 18:34:10 +0000
X-Mailer: exmh version 2.5+CL 07/13/2001 with nmh-1.0.4
To: llp@cs.princeton.edu
cc: Ian.Pratt@cl.cam.ac.uk, Steven.Hand@cl.cam.ac.uk,
      Tim.Harris@cl.cam.ac.uk
Subject:
Mime-Version: 1.0
Content-Type: multipart/mixed ; boundary="==_Exmh_-16020224590"
Date: Wed, 30 Oct 2002 18:34:09 +0000
From: Andrew Warfield <Andrew.Warfield@cl.cam.ac.uk>
Message-Id: <E186xfO-0006yt-00@wisbech.cl.cam.ac.uk>
Resent-To: tim.harris@gmail.com
Resent-Date: Mon, 31 May 2004 20:52:01 +0100

```

<https://mail.google.com/mail/u/0?ik=9ded58fb16&view=om&permmsgid=msg-f%3A1138788268949881537>

1/2

Resent-From: Tim Harris <Tim.Harris@cl.cam.ac.uk>  
Resent-Message-Id: <E1BUspG-0006YK-00@mta1.cl.cam.ac.uk>

--=\_Exmh\_-16020224590  
Content-Type: text/plain; charset=us-ascii

Hi Larry,

As none of the XenoServers folk were able to be in Princeton this week, we thought it might be a good idea to pass along some notes on the directions we are taking regarding isolation... specifically with regard to network resources. I've attached a somewhat hastily prepared document that describes what we have been up to.

I hope the workshop went well, rumors on this end are that it was very good.

Best regards,  
andy.

--=\_Exmh\_-16020224590  
Content-Type: application/pdf ; name="xeno-net-isolation.pdf"  
Content-Description: xeno-net-isolation.pdf  
Content-Transfer-Encoding: base64  
Content-Disposition: attachment; filename="xeno-net-isolation.pdf"

--=\_Exmh\_-16020224590--

# Isolation of Shared Network Resources in XenoServers

Andrew Warfield, Steve Hand, Tim Harris, Ian Pratt  
Computer Laboratory, University of Cambridge

## 1 Introduction

This document presents some issues involved in virtualizing network resources so that they may be shared across a set of isolated virtual machines (VMs). After discussing the issues in design, general details of *Xen*, the XenoServers hypervisor<sup>1</sup> are presented as a specific implementation example. We hope that this presentation will encourage a discussion regarding the best approach to these issues with other researchers involved with similar projects, in particular, designers of isolation architectures for PlanetLab.

The contributions that may be most relevant to efforts to establish a general interface description for network resource isolation are as follows:

1. The presentation of the hypervisor's network system as being a virtualization of a local area network.
2. The explicit use of a packet classifier with the hypervisor that may be configured to appropriately manage traffic across virtual hosts.
3. Efforts to move closer to a description of functionalities that may exist below the virtual network device and the interface to those services being an extended API available to guest VMs.

Throughout the discussion of this design it is important to consider the major trade-offs involved. Primary among these is the balance between the utility provided to virtual machines and the performance overhead imposed on them. Parallel to this performance overhead, and perhaps more important is the complexity imposed on the hypervisor by any additional functionality. As a major design goal of the hypervisor is reliability through simplicity, it seems prudent to give each additional feature careful consideration.

<sup>1</sup>A note on terminology: hypervisors are also described as Virtual Machine Managers (VMM) in other literature

## 2 Overall System Architecture

Figure 1 presents a generic hypervisor/virtual machine architecture. The hypervisor layer serves to virtualize resources and multiplex access from a set of overlying virtual machines. Within the single host, there are now two levels of interface to a given resource: at the bottom level is the raw physical interface between the hypervisor and the device, and above this is the virtual interface that is presented to the virtual machines.




Figure 1: Network Interfaces in a Xenoserver

In considering the virtual network interfaces that are provided to a set of operating system instances, there are many properties that may be desirable. As the hypervisor is multiplexing network resources, the network subsystem may be best understood as being a virtual network switching element. A simple hypervisor implementation might act as a link-layer hub, forwarding all inbound traffic to all virtual machines and multiplexing outbound traffic to the network. Alternatively, the hypervisor may act as a switch or router, servicing each VM's traffic differently and possibly providing additional services.




Figure 2: Forwarding Models for ‘Isolated’ Interfaces.

These two models are illustrated in Figure 2. In the first example, the hypervisor presents all traffic to all virtual machines. Although this may be much closer to a pure virtualization of the physical resources, it presents several problems. First, there is a security concern in that each node can see each other node’s traffic. This may have management implications as to whether or not the virtual Ethernet device should allow a promiscuous mode. Second, this model presents a more complicated system structure from a performance standpoint. Incoming packets must be either copied to each VM’s receive queue, incurring an overhead, or alternatively the hypervisor must provide the ability to deliver a common piece of memory as either read-only or copy-on-write to a set of VMs. Although this model’s abstraction is fairly simple – a plain broadcast Ethernet between VMs, it may prove to be the case that providing what is essentially a pure virtualization of the underlying resource imposes an unreasonable cost, both in terms of complexity and performance, on the system.

In the second model, the hypervisor acts as a network switch. A packet classifier is incorporated to “route” individual packets to the appropriate virtual machine. In this model, the hypervisor acts as an IP router, and may provide additional IP-specific services. In addition, promiscuous mode can be implemented by allowing each virtual interface to see only those packets bound for the associated VM; this behaviour is identical to what would be expected if all of the VMs were separate physical machines on a common IP router.

As the vast majority of traffic is likely to be TCP/IP-based, there is an understandable benefit to providing additional IP services, and the switch model appears to be a reasonable design direction. However, a limitation of this approach is that it does not account for non-IP (and non-ARP) traffic. Developers wishing to explore alternate protocols may prefer the hub model, as it does not modify Ethernet frames before they are forwarded. A hybrid solution to this issue is to act as a router for all regular (IP/ARP) traffic, as described in the second model and as a hub for all other traffic. Developers wishing to bypass the IP routing facilities provided within the hypervisor would be left to use existing IP overlay protocols such as IP over IP.

### 3 Hypervisor Packet Handling

The essential network concerns within the hypervisor can be characterised according to three broad activities: scheduling, multiplexing/demultiplexing, and protection. In the case of PlanetLab, as clients have a vested interest in being able to understand how their hosts are interacting with the network, it seems wise that there be a common design philosophy applied by all isolation system implementors.

#### 3.1 Scheduling

In order to meet the service requirements of specific VMs, the hypervisor must ensure that network traffic is scheduled to meet specified limits. Varying implementations may choose to employ drastically different approaches to scheduling inbound and outbound traffic.

An idealistic goal here might be that all implemented isolation models have identical behaviours in scheduling packets. This is obviously unrealistic and the spec-

ification of a uniform model for packet scheduling may inhibit research in this area. As such, an initial goal here should be that the network system guarantee some degree of resiliency against misuse. As much as possible, the hypervisor should prevent individual hosts from monopolizing resources in such a manner as to impair the functionality of other clients. Additionally, the system may attempt to protect VMs from being flooded by inbound traffic.

### 3.2 Multiplexing/Demultiplexing

Received packets should be delivered only to their target host. Transmitted packets may need to be translated to share a single external IP address.

One approach to this problem is to use a table-based packet classifier/forwarder within the hypervisor to route packets appropriately. The netfilter and IPTables modules within Linux serve as a good example, and form the basis of our implementation, which is described in the next section.

An open issue that stems from the use of a rule based classifier is exactly what operations may be performed as packets are routed. Specifically, we are concerned with how specific matching rules should be, what transformations are allowed, and so on.

### 3.3 Protection

Individual VMs need to be protected from one another and from malicious external traffic. Among other things, this demands that VMs only be allowed to generate IP packets that are valid, and that they not be able to spoof the identity of other hosts. Given the packet classifier approach described above, this behaviour can be achieved fairly easily by either dropping invalid packets, or overwriting the source address and port fields of all outbound packets.

### 3.4 Additional Considerations

In addition to the packet classification functionalities described above, services such as the following may be desirable:

- **Packet Filtering** – The hypervisor may act as a firewall, filtering traffic bound for each virtual machine.
- **Address Translation** – By performing network address translation (NAT) and port forwarding, many virtual machines may share a common external IP address.
- **Traffic Logging** – Details regarding connections may be logged to allow forensic auditing in the case of a specific virtual machine acting maliciously.
- **VM-based Packet Sniffing** – Clients may wish to have some interface approximating promiscuous mode. We suggest above that this is possible, allowing a VM to see all traffic bound for it as if all the VMs were on a router. A packet classifier could be configured to deliver a larger (or even a complete) version of the traffic visible to the external interface to individual VMs. The resolution to this issue is partially a performance concern, as it would likely necessitate multiple copies of inbound message buffers, and partially a political/administrative one, for obvious reasons.

Given the proposed system structure, it should be completely reasonable to provide all of these services. As mentioned previously, the issue that must be considered in each case is the impact that their implementation will have on the efficient processing of VM traffic.

## 4 Network Virtualization in *Xen*

This section describes the design approach that has been taken for the first public release of the XenServers hypervisor, *Xen*. Individual virtual machines may have one or more virtual interfaces, each of which appears as a point-to-point Ethernet link to an IP router. A diagram of the system appears in Figure 3.

The network system within *Xen* consists of a virtual firewall router, which is a rule-based packet classification/forwarding engine (based on the Linux netfilter/IPTables code) responsible for simple, fast packet handling. Additionally, *Xen*'s network system incorporates a network address translation (NAT) module that provides functions such as address translation and port

# Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

## Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

## Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

## Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

## API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

## LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

## FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

## E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.