



Dictionary of Computing

Fourth Edition

Oxford New York Tokyo
OXFORD UNIVERSITY PRESS
1996

STIRLING



Oxford University Press, Walton Street, Oxford OX2 6DP
Oxford New York
Athens Auckland Bangkok Bogota Bombay
Buenos Aires Calcutta Cape Town Dar es Salaam
Delhi Florence Hong Kong Istanbul Karachi
Kuala Lumpur Madras Madrid Melbourne
Mexico City Nairobi Paris Singapore
Taipei Tokyo Toronto
and associated companies in
Berlin Ibadan

Oxford is a trade mark of Oxford University Press

Published in the United States by Oxford University Press Inc., New York

© Market House Books, 1983, 1986, 1990, 1996

First published 1993 Reprinted 1983, 1984, 1985 Second Edition 1986 Third Edition 1990 Reprinted 1990, 1991 (twice), 1992 Fourth Edition 1996

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without the prior permission in writing of Oxford University Press. Within the UK, exceptions are allowed in respect of any fair dealing for the purpose of research or private study, or criticism or review, as permitted under the Copyright, Designs and Patents Act, 1988, or in the case of reprographic reproduction in accordance with the terms of licences issued by the Copyright Licensing Agency. Enquiries concerning reproduction outside those terms and in other countries should be sent to the Rights Department, Oxford University Press, at the address above.

This book is sold subject to the condition that it shall not, by way of trade or otherwise, be lent, re-sold, hired out, or otherwise circulated without the publisher's prior consent in any form of binding or cover other than that in which it is published and without a similar condition including this condition being imposed on the subsequent purchaser.

A catalogue record for this book is available from the British Library

Library of Congress Cataloging in Publication Data (Data available) ISBN 0-19-853855-3

Text prepared by Market House Books Ltd, Aylesbury Printed in Great Britain by Biddles Ltd, Guildford & King's Lynn

D164



ture, which in turn represents a *graph. If A is the adjacency matrix corresponding to a given graph G, then

 $a_{ij} = 1$

if there is an edge from vertex i to vertex j in G; otherwise

 $a_{ij} = 0$

If G is a directed *graph then

 $a_{ij} = 1$

if there is an edge directed from vertex i to vertex j; otherwise

 $a_{ij} = 0$

If the vertices of the graph are numbered 1,2,...m, the adjacency matrix is of a type $m \times m$. If

 $A \times A \times ... \times A$ (p terms, $p \le m$)

is evaluated, the nonzero entries indicate those vertices that are joined by a *path of length p; indeed the value of the (i,j)th entry of A^p gives the number of paths of length p from the vertex i to vertex j. By examining the set of such matrices,

$$p = 1, 2, ..., m-1$$

it can be determined whether two vertices are connected.

It is also possible for adjacency matrices to be formed from *Boolean matrices.

adjacency structure (adjacency list) A means of representing a *graph. The adjacency structure corresponding to a *path G is the set

 $\{Adj(v) \mid v \text{ is a vertex in } G\}$

If G is an undirected graph, then a vertex w is in Adj(v) if and only if there is an edge in G between v and w; if G is a directed graph, then w is in Adj(v) if and only if there is an edge in G directed from v to w.

ADP Abbrev. for automatic data processing. See data processing.

affine mapping (affine transformation) A mapping from one coordinate system to another under which parallel lines remain parallel and ratios of collinear points are preserved. An affine mapping can be decomposed into linear transformations (rotation, scaling, and shear) and translation.

AFIPS American Federation of Information Processing Societies, founded in 1961 to provide a structure for professional societies with a primary interest in information processing to join together in order to advance the state of the art. AFIPS was dissolved in 1990. In 1991 its two principal members, the *ACM and the *IEEE Computer Society, formed a joint committee known as FOCUS (Focus on Computing in the US), which represents the US in *IFIP.

AFL Abbrev. for abstract family of languages.

agenda mechanism A control scheme often used in *knowledge-based systems and *blackboard systems to order the sequence of action execution. While the system is running, inference processes may examine the agenda and manipulate it by the dynamic addition, removal, and reordering of items.

agent An autonomous system that receives information from its environment, processes it, and performs actions on that environment. Agents may have different degrees of intelligence or rationality, and may be software, hardware, or both.

Software agents operate in symbolic environments, and perceive and act upon strings of symbols; examples include personal assistant agents that enhance and customize facilities for computer users, and *data mining agents that search for interesting patterns in large databases. In a *distributed system, the agent for a *remote procedure call is in a different computer from the caller; its environment is the network and the procedure body. A robot (see robotics) is an example of an agent that perceives its physical environment through sensors and acts through effectors.

AGV Abbrev. for autonomous guided vehicle.

Al Abbrev. for artificial intelligence.

Aitken's Δ^2 **process** A method to convert any convergent sequence $\{x_n\}$ into a more rapidly convergent sequence $\{x_n'\}$. For linearly converging sequences the formula is:

 $x_n' = x_n - (x_{n+1} - x_n)^2 / (x_{n+2} - 2x_{n+1} + x_n)$

AIX An IBM version of *UNIX.

ALARP principle A principle that is associated with the design and development of safety systems, and captures the notion that the risk to individuals, society, and the environment should be As Low As Reasonably Possible. See also safety-critical system, safety-related system.

