

[Bright Data](#) > [Tools & Integrations](#) > [Integration](#)

## Articles in this section



# How do I integrate Bright Data into a web browser automation tool?

1 month ago · Updated

[Follow](#)

Integrating Bright Data into a web browser automation tool such as Selenium or Puppeteer can be done by route to Bright Data super proxy port which is `zproxy.lum-superproxy.io:22225` and authenticate with your Bright Data Zone credentials.

The username and password of the specific Zone can be find in the [API examples](#).

Watch Bright Data [Browser Automation webinar](#)

### Integrating Bright Data super proxy with Selenium:

```
const {Builder, By, Key, until} = require('selenium-webdriver');
const proxy = require('selenium-webdriver/proxy');

(async function example(){
  let driver = await new Builder().forBrowser('firefox').setProxy(proxy.manual({
    http: 'zproxy.lum-superproxy.io:22225',
    https: 'zproxy.lum-superproxy.io:22225'
  })).build()

  try {
```

The Data Company Technologies Inc. v. Bright Data Ltd.

```
        driver.switchTo().alert().sendKeys('lum-customer-USERNAME'+Key.TAB+'PAS
        driver.switchTo().alert().accept();
    } finally {
        await driver.quit();
    }
}());
```

**NOTE:** The latest Firefox version that supports the above code is **66.0.5**. Newer versions support **IP:PORT** format, so using newer Firefox versions can be done [through Proxy Manager configuration](#).

### Integrating Bright Data super proxy with Puppeteer:

```
const puppeteer = require('puppeteer');

(async () => {
    const browser = await puppeteer.launch({
        headless: false,
        args: ['--proxy-server=zproxy.lum-superproxy.io:22225']
    });
    const page = await browser.newPage();
    await page.setUserAgent('Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit
    await page.authenticate({
        username: 'lum-customer-USERNAME',
        password: 'PASSWORD'
    });
    await page.goto('http://lumtest.com/myip.json');
    await page.screenshot({path: 'example.png'});
    await browser.close();
})();
```

Watch video: [connecting Puppeteer with Bright Data super proxy](#)

Note: Chromium user-agent include "HeadlessChrome" that need to be replaced as shown in the example above using `setUserAgent`.



Was this article helpful?

Yes

No

0 out of 0 found this helpful

Have more questions? [Submit a request](#)

---

Return to top ^

---

### Related articles

[Selenium Proxy Integration with Bright Data](#)

[How do I integrate Bright Data as my proxy network?](#)

[How can I use Proxy credentials type: http://host:port || IP:PORT ?](#)

[How to integrate the Proxy Manager with Selenium?](#)

[How do I configure IP rotation when using Bright Data?](#)

---

Bright Data

English (US) ▾