



(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
11.11.2009 Bulletin 2009/46

(51) Int Cl.:
H01F 1/147^(2006 01) H01F 1/20^(2006 01)

(21) Application number: 09005258.0

(22) Date of filing: 09.04.2009

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL
PT RO SE SI SK TR
Designated Extension States:
AL BA RS

- Wakayama, Katsuhiko
Tokyo 103-8272 (JP)
- Moro, Hideharu
Tokyo 103-8272 (JP)
- Sato, Naoyoshi
Tokyo 103-8272 (JP)
- Hirai, Yoshihito
Tokyo 103-8272 (JP)
- Murayoshi, Toshihisa
Tokyo 103-8272 (JP)

(30) Priority: 23.04.2008 JP 2008112863

(71) Applicant: TDK Corporation
Tokyo 103-8272 (JP)

(74) Representative: Grünecker, Kinkeldey,
Stockmair & Schwanhäusser
Anwaltssozietät
Leopoldstrasse 4
80802 München (DE)


(72) Inventors:
• Matsukawa, Atsuhito
Tokyo 103-8272 (JP)

(54) Flat soft magnetic material and process for its production

(57) A flat soft magnetic material to be used for a noise-suppressing magnetic sheet, wherein the 50% particle size D_{50} (μm), coercive force H_c (A/m) and bulk density BD (Mg/m^3) of the flat soft magnetic material satisfy the following formula (1).

$$D_{50}/(H_c \times BD) \geq 1.5 \quad (1)$$

Fig.1



P 2 117 017 A1

Description**BACKGROUND OF THE INVENTION**5 **Field of the Invention**

[0001] The present invention relates to a flat soft magnetic material to be used in a noise-suppressing magnetic sheet, and to a process for its production.

10 **Related Background Art**

[0002] As the operating speeds of digital circuits have increased in recent years, the electromagnetic noise emitted from circuits has shifted more toward the high-frequency band. Such noise arises from malfunctioning of the devices themselves resulting from internal interference, or malfunctioning of other devices resulting from external interference.

15 Further increased packaging density is also becoming necessary in recent years in order to achieve lighter-weight, thinner and smaller digital circuit-mounted devices. Electromagnetic shielding materials capable of shielding noise continue to be developed, and methods have been proposed wherein noise-suppressing parts comprising sheets of oriented and dispersed soft magnetic materials are placed near electronic circuits that are the sources of noise.

[0003] Soft magnetic materials are used in such noise-suppressing sheets, and it is known that a noise-suppressing effect can be achieved in a wide frequency band if the soft magnetic material is thin and flat.

20 [0004] Methods that have been disclosed for fabrication of flat soft magnetic materials include using sendust materials produced by water atomization, as a method for producing flaky or flat Fe-Si-A1 alloy powder, in JP No. S62-238305 A (Document 1) and JP No. H1-294802 A (Document 2), for example. Also, JP No. 2003-332113 A (Document 3) and JP No. 2005-123531 A (Document 4) disclose using flat soft magnetic metal powders, or materials produced by gas atomization. In addition, JP No. 2001-303111 A (Document 5) discloses a method in which a fatty acid and an organic solvent such as an alcohol are included during pulverization in the mechanical flat working of a soft magnetic metal powder grinding medium by atomization using a pulverizer. Finally, JP No. H5-98301 A (Document 6) discloses, as an example, flattening treatment of sendust powder produced by water atomization together with ethanol, using an attritor.

30 **SUMMARY OF THE INVENTION**

[0005] Documents 1, 2, 5 and 6 deal with soft magnetic materials for use in magnetic cards, while Documents 3 and 4 focus on the oxygen contents of the soft magnetic materials. None of the soft magnetic materials produced by the processes described in Documents 1-6 have had high enough magnetic permeability to exhibit sufficient sheet properties when they are used as noise-suppressing magnetic sheets.

35 [0006] It is therefore an object of the present invention to provide a flat soft magnetic material that can be used to form a noise-suppressing magnetic sheet with sufficiently high magnetic permeability, as well as a process for its production.

[0007] The invention provides a flat soft magnetic material to be used for a noise-suppressing magnetic sheet, wherein the 50% particle size D_{50} (μm), coercive force H_c (A/m) and bulk density BD (Mg/m^3) of the flat soft magnetic material satisfy the following formula (1).

$$D_{50}/(H_c \times \text{BD}) \geq 1.5 \quad (1)$$

45 [0008] By using a flat soft magnetic material satisfying these conditions, it is possible to form a noise-suppressing magnetic sheet with sufficiently high magnetic permeability. The magnetic permeability at high frequency can be represented as the complex magnetic permeability ($\mu = \mu' - j\mu''$) where μ' is the real permeability and μ'' is the imaginary permeability. The magnetic shielding effect is dependent on the size of the real permeability μ' , while the noise-absorbing effect is dependent on the size of the imaginary permeability μ'' .

50 [0009] The noise-suppressing magnetic sheet performs noise absorption utilizing the imaginary part μ'' of the complex magnetic permeability of the magnetic material in the frequency band in which noise is generated, and the maximum value of μ'' is larger with a larger μ' , at low frequency. Such a high magnetic permeability (high μ) sheet can be obtained by high density packing of flat powder with a low coercive force H_c and a large particle size.

55 [0010] The present inventors have conducted diligent research on the relationship between the physical properties and the magnetic permeability μ' (sheet property) of flat powder in a magnetic sheet produced using flat powder obtained by flattening of soft magnetic alloy powder, and the research has shown that a larger value of $D_{50}/(H_c \times \text{BD})$ for the flat powder results in a larger μ' of the magnetic sheet, given a constant fill factor for the magnetic material. Because the

Hc value tends to be smaller with a larger flat powder particle size, the inventors believe that using a sufficiently flattened magnetic material with a large particle size is an essential condition for obtaining a magnetic sheet with a high μ .

[0011] The flat soft magnetic material of the invention preferably has an aspect ratio of 20 or greater and a D_{50} of 50 μm or greater. By using such a flat soft magnetic material, it is possible to form a noise-suppressing magnetic sheet with even higher magnetic permeability.

[0012] The flat soft magnetic material preferably contains an Fe-Si-Al based alloy (hereinafter also referred to as "sendust"). Sendust has sufficiently low coercive force and can therefore further increase the magnetic permeability. In addition, since sendust does not contain expensive metals, it provides the further advantage of cost reduction.

[0013] The invention provides a process for production of the aforementioned flat soft magnetic material, which process comprises a heat treatment step in which soft magnetic alloy powder produced by an atomization method is heat treated in an inert atmosphere at 800-1200°C to obtain heat treated powder, and a flattening step in which the heat treated powder is flattened in the presence of an organic solvent.

[0014] The production process described above allows production of a flat soft magnetic material that can be used to form a noise-suppressing magnetic sheet with a sufficiently high magnetic permeability.

[0015] According to the production process of the invention, the porosity of the heat treated powder is preferably no greater than 0.15 m^3/Mg and the average crystal grain size is preferably at least 6 μm . By using such heat treated powder it is possible to obtain a flat soft magnetic material with an even smaller Hc value.

[0016] In the production process described above, the organic solvent is preferably a C2-4 monohydric alcohol in order to obtain a high yield of flat powder with a large particle size, without using a flattening aid. The alcohol used for flattening will thus be easy to recover and reutilize.

[0017] According to the invention it is possible to provide a flat soft magnetic material that can be used to form a noise-suppressing magnetic sheet with sufficiently high magnetic permeability, as well as a process for its production.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Fig. 1 is a graph showing the results of measurement of a mercury porosimeter for Fe-Si-Al based alloy powder prepared by atomization; and

Fig. 2 is a graph showing the relationship between $D_{50}/(\text{Hc} \times \text{BD})$ for the flat soft magnetic material and μ' for the magnetic sheet.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

<Flat soft magnetic material>

[0019] The flat soft magnetic material of this embodiment (hereinafter also referred to as "flat powder") has a 50% particle size D_{50} (μm), coercive force Hc (A/m) and bulk density BD (Mg/m^3) that satisfy the following formula (1).

$$D_{50}/(\text{Hc} \times \text{BD}) \geq 1.5 \quad (1)$$

[0020] The flat soft magnetic material can be produced by flattening soft magnetic alloy powder.

[0021] The soft magnetic alloy powder is preferably an alloy with a low coercive force, more preferably an Fe-Si-Al based alloy, known as "sendust" or an Fe-Ni based alloy, known as "permalloy", and even more preferably sendust, since it can result in an even smaller Hc value.

[0022] The soft magnetic alloy powder may be produced by a water atomization method, gas atomization method or gas-water atomization method. A water atomization method is a method in which high-pressure water is injected into molten metal of a soft magnetic alloy falling as starting material from a nozzle, for water-cooling to solidify and powderize the soft magnetic alloy. A gas atomization method is a method in which high-pressure gas is injected into molten metal of a soft magnetic alloy falling as starting material from a nozzle, for air-cooling to solidify and powderize the soft magnetic alloy. The gas used may be air or an inert gas, but preferably an inert gas is used for sendust. A gas-water atomization method is a combination of gas atomization and water atomization, in which high-pressure gas is injected into molten metal of a soft magnetic alloy falling as starting material from a nozzle, prior to water-cooling to solidify and powderize the soft magnetic alloy.

[0023] According to the invention, it is preferred to use soft magnetic alloy powder produced by a gas atomization or gas-water atomization method, because these allow the porosity to be reduced.

[0024] While a larger particle size of the flat powder allows the μ' of the magnetic sheet to be increased given the same fill factor, this also makes high-density packing more difficult and roughens the sheet surface, and therefore the

50% particle size D_{50} of the soft magnetic alloy powder is preferably about 50-100 μm .

[0025] The flat soft magnetic material can be produced by a method comprising a heat treatment step in which soft magnetic alloy powder is heat treated in an inert atmosphere at 800-1200°C to obtain heat treated powder, and a flattening step in which the heat treated powder is flattened in the presence of an organic solvent. This process will now be explained.

(Heat treatment step)

[0026] As pretreatment prior to flattening of the soft magnetic alloy powder, the soft magnetic alloy powder obtained by different atomization methods is heated treated at a prescribed temperature in an inert atmosphere containing an introduced inert gas such as argon gas, to obtain a heat treated powder.

[0027] The heat treatment temperature is 800-1200°C, and more preferably 900-1100°C. Heat treatment in this temperature range can increase the crystal grain size of the soft magnetic alloy powder. If the treatment temperature exceeds 1200°C, the soft magnetic alloy powder will undergo extensive aggregation or sintering, thus hampering the flattening process.

[0028] The heat treatment time is preferably about 10 minutes-5 hours and more preferably 1-3 hours. A heat treatment time of less than 10 minutes will not result in a sufficiently large crystal grain size, while a time of greater than 5 hours will not result in any greater crystal grain size and thus lowers productivity.

[0029] The porosity of the heat treated powder is preferably no greater than 0.15 m^3/Mg , more preferably no greater than 0.10 m^3/Mg and even more preferably no greater than 0.07 m^3/Mg . A lower porosity will result in an increased 50% particle size of the soft magnetic material after flattening, thus tending to increase the μ' of the magnetic sheet. The porosity of the heat treated powder can be measured with a mercury porosimeter.

[0030] Fig. 1 is a graph showing the measurement results for Fe-Si-Al based alloy powder prepared by different atomization methods, using a mercury porosimeter. As seen in Fig. 1, the porosity of the soft magnetic alloy powder depends on the atomization method, with increasing porosity in the following order: gas atomization < gas-water atomization < water atomization. The change in porosity of the soft magnetic alloy powder due to heat treatment temperature is minimal.

[0031] The average crystal grain size of the heat treated powder is preferably at least 6 μm , more preferably at least 8 μm and even more preferably at least 9 μm . A average crystal grain size of less than 6 μm will result in a small 50% particle size of the flat soft magnetic material, thus tending to decrease the μ' of the magnetic sheet. The average crystal grain size is the value determined by image analysis when the soft magnetic alloy powder or heat treated powder is embedded in a resin, mirror-polished and then etched, and photographed with a scanning electron microscope (SEM).

(Flattening step)

The heat treated powder is then flattened.

[0032] The flattening method is not particularly restricted and may be carried out, for example, using an attritor, ball mill, vibrating mill or the like. An attritor is preferably used to allow mixing and pulverization of the starting powder in a shorter time than with a ball mill or vibrating mill. The flattening is preferably carried out in a wet system using an organic solvent.

[0033] The organic solvent used may be, for example, toluene, hexane, acetone, methanol or a C2-4 monohydric alcohol. C2-4 monohydric alcohols include ethanol, 1-propanol, 2-propanol, 1-butanol, 2-butanol, isobutanol and t-butanol.

[0034] The amount of organic solvent added is preferably 200-2000 parts by weight and more preferably 500-1000 parts by weight with respect to 100 parts by weight of the heat treated powder. If the organic solvent is added at less than 200 parts by weight the particle size of the flat powder will tend to be reduced, and if it is added at greater than 2000 parts by weight the treatment time will be lengthened, thus lowering the productivity.

[0035] Even when a friable soft magnetic alloy powder is used, it is possible to obtain a high yield of sufficiently flattened flat powder with a large particle size, by adding the organic solvent. Sendust is easily crushed, and it has been difficult to obtain high yields of sufficiently flattened flat powder with large particle sizes by conventional methods. According to the invention, it is possible to accomplish satisfactory flattening even when using sendust, and to obtain a flat soft magnetic material with a average particle size of 50 μm or greater that is suitable for use in a noise-suppressing magnetic sheet.

[0036] A flattening aid may be used together with the organic solvent in order to increase the particle size of the flat powder. Fatty acids such as stearic acid are examples of flattening aids that may be used. The amount of flattening aid added is preferably 0.1-5 parts by weight and more preferably 0.5-2 parts by weight with respect to 100 parts by weight of the heat treated powder. Adding the flattening aid at greater than 5 parts by weight will not further increase the particle size of the flat powder, and will also hamper recovery and reuse of the organic solvent while also increasing contamination

of the heat treatment furnace. When a C2-4 monohydric alcohol is used as the organic solvent, a flat powder with a large particle size can be obtained even without adding a flattening aid.

[0037] The flattening treatment is preferably followed by heat treatment of the obtained flat soft magnetic material in an inert atmosphere. This will reduce the coercive force H_c and increase the μ' of the magnetic sheet. The heat treatment temperature in this case is 700-900°C and the treatment time is approximately 10 minutes to 3 hours.

[0038] The aspect ratio (= particle size/thickness) of the flat soft magnetic material produced in the manner described above is preferably 20 or greater, more preferably 20-100 and even more preferably 30-50. An aspect ratio of less than 20 will increase the demagnetizing field, thus lowering the apparent magnetic permeability when the material is used as a magnetic sheet, while an aspect ratio of greater than 100 will lower the fill factor (= flat soft magnetic material volume/magnetic sheet volume), thus tending to lower the magnetic permeability.

[0039] The 50% particle size D_{50} of the flat soft magnetic material is preferably at least 50 μm , more preferably at least 55 μm and even more preferably at least 60 μm . If the D_{50} is less than 50 μm it will be difficult to obtain flat powder with a small holding power H_c , and the real permeability μ' will tend to be smaller. If D_{50} is too large, mixing of the binder resin will be more difficult and production of the magnetic sheet will be hampered, and therefore the upper limit for D_{50} is about 100 μm . The value of D_{50} throughout the present specification was measured by laser diffraction using a dry dispersion unit, employing a "HELOS SYSTEM" by Japan Laser Corp.

[0040] The coercive force H_c of the flat soft magnetic material is preferably no greater than 100A/m and more preferably no greater than 80A/m. If H_c exceeds 100A/m, the μ' value of the magnetic sheet will tend to be smaller. H_c may be measured using a commercially available H_c meter.

[0041] The bulk density BD of the flat soft magnetic material is preferably 0.20-0.60 Mg/m^3 and more preferably 0.25-0.50 Mg/m^3 . If BD is less than 0.20 Mg/m^3 the fill factor will tend to be lower upon sheeting, while if it is greater than 0.60 Mg/m^3 the degree of flattening will be insufficient, thus increasing the demagnetizing field and lowering the apparent magnetic permeability. The BD value can be measured using a bulk specific gravity meter, by the method of JIS K-5101.

[0042] The specific surface area SSA of the flat soft magnetic material is preferably no greater than 1.5 m^2/g and more preferably no greater than 1.0 m^2/g . If the SSA is greater than 1.5 m^2/g , a greater amount of binder resin will be necessary and the fill factor of the magnetic material will tend to be reduced. The SSA value throughout the present specification was measured using a "Macsorb Model-1201" fully automatic specific surface area meter by Mountech Co., Ltd.

[0043] The flat soft magnetic material of the invention has D_{50} , H_c and BD values satisfying the condition represented by formula (1) above, and the value calculated by $D_{50}/(H_c \times \text{BD})$ is 1.5 ($\mu\text{m}/\text{Am}^{-1}/\text{Mgm}^{-3}$) or greater, preferably 2.0 or greater and even more preferably 3.0 or greater.

[0044] Fig. 2 is a graph showing the relationship between $D_{50}/(H_c \times \text{BD})$ for the flat soft magnetic material and μ' for the magnetic sheet. A noise-suppressing magnetic sheet generally performs noise absorption utilizing the imaginary part μ'' of the complex magnetic permeability of the magnetic material in the frequency band in which noise is generated, and maximum value of μ'' is larger with a larger μ' at low frequency. The power of the noise-suppressing sheet can therefore be evaluated based on the size of the value of μ' . A magnetic sheet with a large value for μ' can be obtained by high density packing of flat powder with a low coercive force and a large 50% particle size. When the fill factor of the flat powder in the magnetic sheet is constant, a larger value represented by $D_{50}/(H_c \times \text{BD})$ corresponds to a larger μ' value for the flat powder, so that a more excellent noise-suppressing effect is obtained.

[0045] If $D_{50}/(H_c \times \text{BD})$ is less than 1.5, therefore, the μ' value of the magnetic sheet will be smaller and the noise-suppressing effect may be inadequate.

<Noise-suppressing magnetic sheet>

[0046] A magnetic sheet may be formed using the flat soft magnetic material described above. There are no particular restrictions on the method of forming the magnetic sheet, and the following is an example.

[0047] The flat soft magnetic material and binder resin may be kneaded together and subjected to press molding or extrusion molding to form a sheet. Alternatively, the flat soft magnetic material and binder resin may be dispersed in an organic solvent to produce a slurry, and the slurry cast as a film to a prescribed thickness on a support base by doctor blading and then dried and rolled with a calender roll to form a sheet.

[0048] The thickness of the magnetic sheet will be about 0.05-2 mm. Since the noise-suppressing effect is proportional to the thickness of the magnetic sheet, it will be difficult to obtain a satisfactory effect if the thickness of the magnetic sheet is less than 0.05 mm. On the other hand, a magnetic sheet thickness of greater than 2 mm will result in more difficult loading into the narrow spaces inside the packages of electrical equipment.

[0049] The fill factor of the flat soft magnetic material in the magnetic sheet is preferably 30-60 vol% and more preferably 40-50 vol%. A fill factor of less than 30 vol% will result in a lower noise-suppressing effect, while a fill factor of greater than 60 wt% will prevent the soft magnetic material from being firmly bound by the binder resin, thus lowering the magnetic sheet strength.

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.