

DC-DC Switching Regulator Analysis

Daniel M. Mitchell

Advanced Technology and Engineering Department Collins Defense Communications Rockwell International Corporation Cedar Rapids

Adjunct Instructor Department of Electrical and Computer Engineering University of lows lows City

McGraw-Hill Book Company

New York St. Louis San Francisco Auckland Bogotá Hamburg London Madrid Mexico Milan Montreal New Delhi Panama Paris São Paulo Singapore Sydney Tokyo Toronto

Library of Congress Cataloging-in-Publication Data

Mitchell, Daniel M. DC-DC switching regulator analysis.

 Electronic apparatus and appliances—Power supply—Direct current. I. Title. TK7868.P6M58 1988 621.381'044 87-16976 ISBN 0-07-042597-3

Copyright © 1988 by McGraw-Hill, Inc. All rights reserved. Printed in the United States of America. Except as permitted under the United States Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a data base or retrieval system, without the prior written permission of the publisher.

1234567890 DOC/DOC 89210987

ISBN 0-07-042597-3

The editors for this book were Daniel A. Gonneau and Lucy Mullins, the designer was Naomi Auerboeh, and the production supervisor was Dianne Walber. It was set in Century Schoolbook by Techna Type, Inc.

Printed and bound by R. R. Donnelley & Sons Company.

38 DC-DC Switching Regulator Analysis

Figure 3.2 shows a simple PWM controller with a fixed-frequency fixed-amplitude sawtooth signal applied to the basic buck converter. The width of the PWM ON pulse is the time between the reset of the sawtooth generator and the intersection of the error voltage with the positive-going sawtooth signal, or ramp. If v_e is the error voltage amplitude, which is assumed to change slowly with respect to the switching frequency, and V_p is the sawtooth voltage amplitude, then the duty factor can be approximated by the continuous expression

$$d = \frac{v_e}{V_p}$$
(3.2)

