

INTERNATIONAL TELECOMMUNICATION UNION



G.992.1 (06/99)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

Digital transmission systems – Digital sections and digital line system – Access networks

Asymmetric digital subscriber line (ADSL) transceivers

ITU-T Recommendation G.992.1

(Previously CCITT Recommendation)

RM

ITU-T G-SERIES RECOMMENDATIONS

TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
INTERNATIONAL ANALOGUE CARRIER SYSTEM	
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER- TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TESTING EQUIPMENTS	
TRANSMISSION MEDIA CHARACTERISTICS	G.600–G.699
DIGITAL TRANSMISSION SYSTEMS	
TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
General	G.900–G.909
Parameters for optical fibre cable systems	G.910–G.919
Digital sections at hierarchical bit rates based on a bit rate of 2048 kbit/s	G.920–G.929
Digital line transmission systems on cable at non-hierarchical bit rates	G.930–G.939
Digital line systems provided by FDM transmission bearers	G.940–G.949
Digital line systems	G.950–G.959
Digital section and digital transmission systems for customer access to ISDN	G.960–G.969
Optical fibre submarine cable systems	G.970–G.979
Optical line systems for local and access networks	G.980–G.989
Access networks	G.990–G.999

For further details, please refer to ITU-T List of Recommendations.

ASYMMETRIC DIGITAL SUBSCRIBER LINE (ADSL) TRANSCEIVERS

Summary

This Recommendation describes Asymmetric Digital Subscriber Line (ADSL) Transceivers on a metallic twisted pair that allows high-speed data transmission between the network operator end (ATU-C) and the customer end (ATU-R). This Recommendation provides a variety of bearer channels in conjunction with one of three other services dependent on the environment:

- 1) ADSL transmission simultaneously on the same pair with voice (band) service;
- 2) ADSL transmission simultaneously on the same pair with G.961 (Appendix I or II) ISDN services; or
- 3) ADSL transmission on the same pair with voiceband transmission and with TCM-ISDN (G.961 Appendix III) in an adjacent pair.

Systems allow approximately 6 Mbit/s downstream and approximately 640 kbit/s upstream data rates depending on the deployment and noise environment.

This Recommendation specifies the physical layer characteristics of the Asymmetric Digital Subscriber Line (ADSL) interface to metallic loops.

This Recommendation has been written to help ensure the proper interfacing and interworking of ADSL transmission units at the customer end (ATU-R) and at the network operator end (ATU-C) and also to define the transport capability of the units. Proper operation shall be ensured when these two units are manufactured and provided independently. A single twisted pair of telephone wires is used to connect the ATU-C to the ATU-R. The ADSL transmission units must deal with a variety of wire pair characteristics and typical impairments (e.g. crosstalk and noise).

An ADSL transmission unit can simultaneously convey all of the following: downstream simplex bearers, duplex bearers, a baseband analogue duplex channel, and ADSL line overhead for framing, error control, operations and maintenance. Systems support a minimum of 6.144 Mbit/s downstream and 640 kbit/s upstream.

This Recommendation includes mandatory requirements, recommendations and options; these are designated by the words "shall", "should" and "may" respectively. The word "will" is used only to designate events that take place under some defined set of circumstances.

Two categories of performance are specified. Category I performance is required for compliance with this Recommendation; performance enhancement options are not required for category I equipment. Category II is a higher level of performance (i.e. longer lines and greater impairments). Category II performance and characteristics are not required for compliance with this Recommendation.

This Recommendation defines several optional capabilities and features:

• echo cancellation;

RM

- trellis coded modulation;
- dual latency;
- transport of a network timing reference;
- transport of STM and/or ATM;
- reduced overhead framing modes.

It is the intention of this Recommendation to provide, by negotiation during initialization, for U-interface compatibility and interoperability between transceivers complying to this Recommendation and between transceivers that include different combinations of options.

Source

DOCKE

ITU-T Recommendation G.992.1 was prepared by ITU-T Study Group 15 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on 22 June 1999.

Recommendation G 992.1 (06/99)

FUREWURD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2000

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Recommendation G.992.1 (06/99)

RM

ii

Find authenticated court documents without watermarks at docketalarm.com.

0011121120

Page

1	Scope	1
1.1	System reference model	2
1.2	Objectives	2
2	References	3
3	Definitions	3
4	Abbreviations	6
5	Reference Models	9
5.1	ATU-C transmitter reference models	9
	5.1.1 ATU-C transmitter reference model for STM transport	10
	5.1.2 ATU-C transmitter reference model for ATM transport	11
5.2	ATU-R transmitter reference models	12
	5.2.1 ATU-R transmitter reference model for STM transport	12
	5.2.2 ATU-R transmitter reference model for ATM transport	13
5.3	ATU-C/R transmitter timing model (Annex C only)	13
6	Transport capacity	14
6.1	Transport of STM data	15
6.2	Transport of ATM data	16
6.3	ADSL system overheads and total bit rates	17
7	ATU-C functional characteristics	18
7.1	STM Transmission Protocol Specific functionalities	19
	7.1.1 ATU-C input and output V interfaces for STM transport	19
	7.1.2 Downstream simplex channels – bit rates	19
	7.1.3 Downstream/upstream duplex channels – bit rates	19
	7.1.4 Payload transfer delay	20
	7.1.5 Framing Structure for STM transport	20
7.2	ATM Transport Protocol Specific functionalities	20
	7.2.1 ATU-C input and output V interface for ATM transport	20
	7.2.2 Payload transfer delay	21
	7.2.3 ATM Cell specific functionalities	21
	7.2.4 Framing Structure for ATM transport	23
7.3	Network timing reference (NTR)	24
	7.3.1 Need for NTR	24
	7.3.2 Transport of the NTR	24
7.4	Framing	25
	7.4.1 Data symbols	25

Recommendation G 992.1 (06/99)

iii

DOCKET



Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time** alerts and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.

