


Power Supply

Design Guide for Desktop Platform Form Factors

Revision 1.1

March 2007



INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. Intel products are not intended for use in medical, life saving, or life sustaining applications.

Intel may make changes to specifications and product descriptions at any time, without notice.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

This document contains information on products in the design phase of development. Do not finalize a design with this information. Revised information will be published when the product is available. Verify with your local sales office that you have the latest datasheet before finalizing a design.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.


Hyper-Threading Technology requires a computer system with an Intel® Pentium® 4 processor supporting HT Technology and a Hyper-Threading Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See <<http://www.intel.com/info/hyperthreading>> for more information including details on which processors support HT Technology

Intel, Celeron, Intel NetBurst, Xeon and the Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2007, Intel Corporation.

*Other names and brands may be claimed as the property of others.




Contents

1	Introduction	11
1.1	Reference Documentation.....	11
1.2	Terminology	12
2	Platform Configurations	15
2.1	Digital Home and Digital Office Platform Configurations - RECOMMENDED	15
3	Electrical	21
3.1	AC Input - REQUIRED	21
3.1.1	Input Over Current Protection - REQUIRED	21
3.1.2	Inrush Current - REQUIRED	21
3.1.3	Input Under Voltage - REQUIRED	21
3.2	DC Output - REQUIRED	22
3.2.1	DC Voltage Regulation	22
3.2.2	Output Transient Response - REQUIRED	22
3.2.3	Remote Sensing - REQUIRED	23
3.2.4	Other Low Power System Requirements - RECOMMENDED	23
3.2.5	Output Ripple Noise - REQUIRED	23
3.2.6	Capacitive Load - REQUIRED.....	24
3.2.7	Closed Loop Stability - REQUIRED	24
3.2.8	+5 VDC / +3.3 VDC Power Sequencing - REQUIRED	24
3.2.9	Voltage Hold-up Time - REQUIRED	25
3.3	Timing, Housekeeping and Control - REQUIRED.....	25
3.3.1	PWR_OK	25
3.3.2	Power-up Cross Loading Condition	26
3.3.3	PS_ON#.....	26
3.3.4	+5 VSB.....	27
3.3.5	Power-on Time.....	27
3.3.6	Rise Time.....	27
3.3.7	Overshoot at Turn-on / Turn-off	28
3.4	Reset after Shutdown	28
3.4.1	+5 VSB at Power-down	28
3.5	Output Protection - REQUIRED	28
3.5.1	Over Voltage Protection.....	28
3.5.2	Short Circuit Protection	28
3.5.3	No-load Situation	29
3.5.4	Over Current Protection	29
3.5.5	Over Temperature Protection	29
3.5.6	Output Bypass	29
3.5.7	Separate Current Limit for 12V2 - RECOMMENDED.....	29
3.5.8	Overall Power Supply Efficiency and ENERGY STAR	29
4	Mechanical	33
4.1	Labeling and Marking - RECOMMENDED.....	33
4.2	Connectors - REQUIRED	33
4.2.1	AC Connector	33
4.2.2	DC Connectors.....	33
4.2.2.1	Main Power Connector	34
4.2.2.2	Peripheral Connectors.....	35
4.2.2.3	Floppy Drive Connector.....	35
4.2.2.4	+12 V Power Connector	36
4.2.2.5	Serial ATA* Power Connectors	36
4.3	Airflow and Fans - RECOMMENDED	37



4.3.1	Fan Location and Direction	37
4.3.2	Fan Size and Speed	37
4.3.3	Venting	38
5	Acoustics	39
5.1	Acoustics - RECOMMENDED	39
6	Environmental	41
6.1	Temperature - RECOMMENDED	41
6.1.1	Thermal Shock (Shipping)	41
6.2	Humidity - RECOMMENDED	41
6.3	Altitude - RECOMMENDED	41
6.4	Mechanical Shock - RECOMMENDED	41
6.5	Random Vibration - RECOMMENDED	41
7	Electromagnetic Compatibility	43
7.1	Emissions - REQUIRED	43
7.2	Immunity - REQUIRED	43
7.3	Input Line Current Harmonic Content - OPTIONAL	43
7.4	Magnetic Leakage Fields - REQUIRED	44
7.5	Voltage Fluctuations and Flicker - REQUIRED	44
8	Safety	45
8.1	North America - REQUIRED	45
8.2	International - REQUIRED	45
8.3	Proscribed Materials	46
8.4	Catastrophic Failure Protection - REQUIRED	46
9	Reliability	47
9.1	Reliability - RECOMMENDED	47
10	CFX12V Specific Guidelines 1.4	49
10.1	Typical Power Distribution - RECOMMENDED	49
10.2	Physical Dimensions - REQUIRED	53
11	LFX12V Specific Guidelines 1.2	55
11.1	Typical Power Distribution - RECOMMENDED	55
11.2	Physical Dimensions - REQUIRED	58
12	ATX12V Specific Guidelines 2.3	63
12.1	Typical Power Distribution - RECOMMENDED	63
12.2	Physical Dimensions - REQUIRED	72
13	SFX12V Specific Guidelines 3.2	75
13.1	Typical Power Distribution - RECOMMENDED	75
13.2	Lower Profile Package - Physical Dimensions - REQUIRED	79
13.3	Fan Requirements - REQUIRED	79
13.4	Top Fan Mount Package - Physical Dimensions - REQUIRED	81
13.5	Fan Requirements - REQUIRED	81
13.6	Reduced Depth Top Mount Fan - Physical Dimensions - REQUIRED	83
13.7	Fan Requirements - REQUIRED	83
13.8	Standard SFX Profile Package - Physical Dimensions - REQUIRED	84
13.9	Fan Requirements - REQUIRED	85
13.10	PS3 Form Factor- Physical Dimensions - REQUIRED	86
13.11	Fan Requirements - REQUIRED	86
14	TFX12V Specific Guidelines 2.3	89
14.1	Typical Power Distribution - RECOMMENDED	89
14.2	Physical Dimensions - REQUIRED	94



14.3	Mounting Options - RECOMMENDED	97
14.4	Chassis Requirements - RECOMMENDED.....	97
15	Flex ATX Specific Guidelines 1.0	99
15.1	Typical Power Distribution - RECOMMENDED	99
15.2	Physical Dimensions - REQUIRED	103

Figures

1	Differential Noise Test Setup	24
2	Power Supply Timing	25
3	PS_ON# Signal Characteristics.....	27
4	PSU Efficiency as Percentage of Output	30
5	PSU Efficiency per Power for 450 W PSU	31
6	PSU Efficiency per Power for 250 W PSU	31
7	Connectors (Pin-side view, not to scale).....	34
8	Serial ATA* Power Connector.....	36
9	Cross Loading Graph for 180 W Configurations.....	49
10	Cross Loading Graph for 220 W Configurations.....	50
11	Cross Loading Graph for 270 W Configuration	51
12	Cross Loading Graph for 300 W Configuration	52
13	CFX12V Mechanical Outline	54
14	Cross Loading Graph for 180 W Configuration	55
15	Cross Loading Graph for 220 W Configurations.....	56
16	Cross Loading Graph for 270 W Configuration	57
17	Mechanical Outline	59
18	Mechanical Details.....	60
19	PSU Slot Feature Detail.....	60
20	Recommended Chassis Tab Feature.....	61
21	Cross Loading Graph for 180 W Configurations.....	63
22	Cross Loading Graph for 220 W Configurations.....	64
23	Cross Loading Graph for 270 W Configurations.....	65
24	Cross Loading Graph for 300 W Configurations.....	66
25	Cross Loading Graph for 350 W Configurations.....	67
26	Cross Loading Graph for 400 W Configurations.....	68
27	Cross Loading Graph for 450 W Configurations.....	69
28	Power Supply Dimensions for Chassis that does not Require Top Venting.....	72
29	Power Supply Dimensions for Chassis that Require Top Venting.....	73
30	Cross Loading Graph for 180 W Configuration	75
31	Cross Loading Graph for 220 W Configurations.....	76
32	Cross Loading Graph for 270 W Configuration	77
33	Cross Loading Graph for 300 W Configuration	78
34	40 mm Profile Mechanical Outline.....	80
35	Chassis Cutout	80
36	Top Mount Fan Profile Mechanical Outline	82
37	Chassis Cutout	83
38	Recessed Fan Mounting.....	83
39	Reduced Depth Top Mount Fan Profile Mechanical Outline	84
40	Chassis Cutout	84
41	60 mm Mechanical Outline	85
42	Chassis Cutout	86
43	PS3 Mechanical Outline.....	87
44	Cross Loading Graph for 180 W Configuration	89
45	Cross Loading Graph for 220 W Configurations.....	90
46	Cross Loading Graph for 270 W Configuration	91

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.