



WPI

REFLECTANCE-BASED PULSE OXIMETER FOR THE CHEST AND WRIST

A Major Qualifying Project Report:

Submitted to the Faculty

Of the

WORCESTER POLYTECHNIC INSTITUTE

In partial fulfillment of the requirements for the

Degree of Bachelor of Science

By

Alexandra Fontaine

Arben Koshi

Danielle Morabito

Nicolas Rodriguez

Submitted on:

Approved by:

Professor Yitzhak Mendelson, Advisor, Dept. of Biomedical Engineering

Authorship

Section	Author
Introduction	Nicolas Rodriguez, Danielle Morabito, Alex Fontaine, Arben Koshi
Literature Review	Nicolas Rodriguez, Danielle Morabito, Alex Fontaine, Arben Koshi
Design Approach	Alex Fontaine, Danielle Morabito
Device Development	Nicolas Rodriguez, Danielle Morabito
Methods	Nicolas Rodriguez, Danielle Morabito
Final Design	Arben Koshi, Nicolas Rodriguez, Danielle Morabito
Results	Alex Fontaine, Arben Koshi
Discussion	Arben Koshi, Alex Fontaine
Summary	Arben Koshi
Conclusion	Arben Koshi
Future Improvements	Arben Koshi, Nicolas Rodriguez
Appendix A	Danielle Morabito
Appendix B	Arben Koshi
Appendix C	Alex Fontaine
Appendix D	Arben Koshi

Abstract

Reflectance-based pulse oximetry is a technique used for noninvasively monitoring the oxygen saturation (SpO₂) and pulse rate (PR). However, there is little supporting evidence that it can accurately collect measurements from the chest and wrist. In this project, a reflectance-based pulse oximeter was built and used to collect measurements while sitting, standing, during self-induced hypoxia, and during self-induced hyperventilation then compared to the measurements taken by a HOMEDIC Deluxe Pulse Oximeter. The prototype was able to accurately measure within an error of $\pm 1\%$ and $\pm 3\%$ for SpO₂ and PR respectively from the wrist while an error of $\pm 1\%$ and $\pm 4\%$ for SpO₂ and PR respectively from the chest.

Acknowledgements

We would like to thank Professor Mendelson for advising this project. We would also like to acknowledge Dr. Adriana Hera and Lisa Wall for their support.

Executive Summary

Oxygen saturation (SpO_2) is the measurement of oxyhemoglobin (HbO_2) in arterial blood. SpO_2 is an important vital measurement because it shows the levels of blood oxygenation. Traditionally, SpO_2 is measured by invasively drawing blood samples. This method, however, is not ideal and it is unable to provide clinicians with real-time measurements. With the need for a noninvasive way to measure SpO_2 , pulse oximetry was developed. The use of this technology allows clinicians to determine SpO_2 in patients that are sedated, anesthetized, unconscious, or unable to regulate their own oxygen supply.

Reflectance-based pulse oximetry allows measurements to be taken from areas of the body in which transmittance based pulse oximetry cannot be applied. In reflectance-based pulse oximetry, the incident light is passed through the skin and is reflected off the subcutaneous tissue and bone. To this day, being able to measure signals from the chest and wrist with one single device has not been successfully achieved. Such a device would allow patients to measure SpO_2 and pulse rate (PR) without hindering their normal day-to-day activities.

The prototype pulse oximeter constructed during this project consists of two hardware components and a programmed LabVIEW Virtual Instrument (VI). The hardware components consist of the sensor and a circuit which produces, collects, and processes photoplethysmographic (PPG) signals. The VI collects the PPG signals produced by the hardware and process them in order to produce numerical results for PR and SpO_2 . The optical sensor is made up of two Light Emitting Diodes (LEDs), a red LED, with a peak emission wavelength of 660 nm, and an infrared emitter with a peak emission wavelength of 940 nm. These LEDs are positioned next to each other in the center of a circular Printed Circuit Board (PCB) and surrounded by 8 photodiodes (PD). The circuitry for the sensor consists of an Arduino Duo Microprocessor which is programmed to light up the red and infrared LEDs intermittently at a frequency of 100Hz. The PDs are connected in photovoltaic mode in order to produce a voltage output. Operational amplifiers are utilized to amplify the photodiode output. Once amplified, the red and infrared PPG signals obtained from the photodetectors are sent through two Sample-and-Hold circuits to separate the signals into their respective alternating current (AC) and direct current (DC) components for further filtering and amplification.

The four input signals sent to the LabVIEW software : AC red, AC infrared, DC red and DC infrared access the VI via a National Instruments (NI) Data Acquisition (DAQ) system. The AC components of the red and infrared PPGs are measured using a peak-to-peak detection algorithm, while the DC components are measured by finding their respective averages. Once the signals are processed, SpO_2 is calculated by obtaining the ratio of the AC and DC components of the red PPG and dividing that by the ratio of the AC and DC components of the infrared PPG. To calculate PR, the frequency of the infrared AC signal is measured using frequency measurement parameters in LabVIEW and then

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.