

Network Working Group
Request for Comments: 1945
Category: Informational

T. Berners-Lee
MIT/LCS
R. Fielding
UC Irvine
H. Frystyk
MIT/LCS
May 1996

Hypertext Transfer Protocol -- HTTP/1.0

Status of This Memo

This memo provides information for the Internet community. This memo does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

IESG Note:

The IESG has concerns about this protocol, and expects this document to be replaced relatively soon by a standards track document.

Abstract

The Hypertext Transfer Protocol (HTTP) is an application-level protocol with the lightness and speed necessary for distributed, collaborative, hypermedia information systems. It is a generic, stateless, object-oriented protocol which can be used for many tasks, such as name servers and distributed object management systems, through extension of its request methods (commands). A feature of HTTP is the typing of data representation, allowing systems to be built independently of the data being transferred.

HTTP has been in use by the World-Wide Web global information initiative since 1990. This specification reflects common usage of the protocol referred to as "HTTP/1.0".

Table of Contents

- 1. Introduction 4
 - 1.1 Purpose 4
 - 1.2 Terminology 4
 - 1.3 Overall Operation 6
 - 1.4 HTTP and MIME 8
- 2. Notational Conventions and Generic Grammar 8
 - 2.1 Augmented BNF 8
 - 2.2 Basic Rules 10
- 3. Protocol Parameters 12

3.2.1	General Syntax	14
3.2.2	http URL	15
3.3	Date/Time Formats	15
3.4	Character Sets	17
3.5	Content Codings	18
3.6	Media Types	19
3.6.1	Canonicalization and Text Defaults	19
3.6.2	Multipart Types	20
3.7	Product Tokens	20
4.	HTTP Message	21
4.1	Message Types	21
4.2	Message Headers	22
4.3	General Header Fields	23
5.	Request	23
5.1	Request-Line	23
5.1.1	Method	24
5.1.2	Request-URI	24
5.2	Request Header Fields	25
6.	Response	25
6.1	Status-Line	26
6.1.1	Status Code and Reason Phrase	26
6.2	Response Header Fields	28
7.	Entity	28
7.1	Entity Header Fields	29
7.2	Entity Body	29
7.2.1	Type	29
7.2.2	Length	30
8.	Method Definitions	30
8.1	GET	31
8.2	HEAD	31
8.3	POST	31
9.	Status Code Definitions	32
9.1	Informational 1xx	32
9.2	Successful 2xx	32
9.3	Redirection 3xx	34
9.4	Client Error 4xx	35
9.5	Server Error 5xx	37
10.	Header Field Definitions	37
10.1	Allow	38
10.2	Authorization	38
10.3	Content-Encoding	39
10.4	Content-Length	39
10.5	Content-Type	40
10.6	Date	40
10.7	Expires	41
10.8	From	42

Berners-Lee, et al

Informational

[Page 2]

RFC 1945

HTTP/1.0

May 1996

10.9	If-Modified-Since	42
10.10	Last-Modified	43
10.11	Location	44
10.12	Pragma	44
10.13	Referer	44
10.14	Server	45
10.15	User-Agent	46
10.16	WWW-Authenticate	46
11.	Access Authentication	47

- 12.1 Authentication of Clients 49
- 12.2 Safe Methods 49
- 12.3 Abuse of Server Log Information 50
- 12.4 Transfer of Sensitive Information 50
- 12.5 Attacks Based On File and Path Names 51
- 13. Acknowledgments 51
- 14. References 52
- 15. Authors' Addresses 54
- Appendix A. Internet Media Type message/http 55
- Appendix B. Tolerant Applications 55
- Appendix C. Relationship to MIME 56
 - C.1 Conversion to Canonical Form 56
 - C.2 Conversion of Date Formats 57
 - C.3 Introduction of Content-Encoding 57
 - C.4 No Content-Transfer-Encoding 57
 - C.5 HTTP Header Fields in Multipart Body-Parts 57
- Appendix D. Additional Features 57
 - D.1 Additional Request Methods 58
 - D.1.1 PUT 58
 - D.1.2 DELETE 58
 - D.1.3 LINK 58
 - D.1.4 UNLINK 58
 - D.2 Additional Header Field Definitions 58
 - D.2.1 Accept 58
 - D.2.2 Accept-Charset 59
 - D.2.3 Accept-Encoding 59
 - D.2.4 Accept-Language 59
 - D.2.5 Content-Language 59
 - D.2.6 Link 59
 - D.2.7 MIME-Version 59
 - D.2.8 Retry-After 60
 - D.2.9 Title 60
 - D.2.10 URI 60

Berners-Lee, et al Informational [Page 3]
 RFC 1945 HTTP/1.0 May 1996

1. Introduction

1.1 Purpose

The Hypertext Transfer Protocol (HTTP) is an application-level protocol with the lightness and speed necessary for distributed, collaborative, hypermedia information systems. HTTP has been in use by the World-Wide Web global information initiative since 1990. This specification reflects common usage of the protocol referred too as "HTTP/1.0". This specification describes the features that seem to be consistently implemented in most HTTP/1.0 clients and servers. The specification is split into two sections. Those features of HTTP for which implementations are usually consistent are described in the main body of this document. Those features which have few or inconsistent implementations are listed in Appendix D.

Practical information systems require more functionality than simple retrieval including search, front-end update, and annotation. HTTP

provided by the Uniform Resource Identifier (URI) [2], as a location (URL) [4] or name (URN) [16], for indicating the resource on which a method is to be applied. Messages are passed in a format similar to that used by Internet Mail [7] and the Multipurpose Internet Mail Extensions (MIME) [5].

HTTP is also used as a generic protocol for communication between user agents and proxies/gateways to other Internet protocols, such as SMTP [12], NNTP [11], FTP [14], Gopher [1], and WAIS [8], allowing basic hypermedia access to resources available from diverse applications and simplifying the implementation of user agents.

1.2 Terminology

This specification uses a number of terms to refer to the roles played by participants in, and objects of, the HTTP communication.

connection

A transport layer virtual circuit established between two application programs for the purpose of communication.

message

The basic unit of HTTP communication, consisting of a structured sequence of octets matching the syntax defined in Section 4 and transmitted via the connection.

Berners-Lee, et al

Informational

[Page 4]

RFC 1945

HTTP/1.0

May 1996

request

An HTTP request message (as defined in Section 5).

response

An HTTP response message (as defined in Section 6).

resource

A network data object or service which can be identified by a URI (Section 3.2).

entity

A particular representation or rendition of a data resource, or reply from a service resource, that may be enclosed within a request or response message. An entity consists of metainformation in the form of entity headers and content in the form of an entity body.

client

An application program that establishes connections for the purpose of sending requests.

user agent

editors, spiders (web-traversing robots), or other end user tools.

server

An application program that accepts connections in order to service requests by sending back responses.

origin server

The server on which a given resource resides or is to be created.

proxy

An intermediary program which acts as both a server and a client for the purpose of making requests on behalf of other clients. Requests are serviced internally or by passing them, with possible translation, on to other servers. A proxy must interpret and, if necessary, rewrite a request message before

Berners-Lee, et al	Informational	[Page 5]
RFC 1945	HTTP/1.0	May 1996

forwarding it. Proxies are often used as client-side portals through network firewalls and as helper applications for handling requests via protocols not implemented by the user agent.

gateway

A server which acts as an intermediary for some other server. Unlike a proxy, a gateway receives requests as if it were the origin server for the requested resource; the requesting client may not be aware that it is communicating with a gateway. Gateways are often used as server-side portals through network firewalls and as protocol translators for access to resources stored on non-HTTP systems.

tunnel

A tunnel is an intermediary program which is acting as a blind relay between two connections. Once active, a tunnel is not considered a party to the HTTP communication, though the tunnel may have been initiated by an HTTP request. The tunnel ceases to exist when both ends of the relayed connections are closed. Tunnels are used when a portal is necessary and the intermediary cannot, or should not, interpret the relayed communication.

cache

A program's local store of response messages and the subsystem that controls its message storage, retrieval, and deletion. A cache stores cachable responses in order to reduce the response time and network bandwidth consumption on future, equivalent requests. Any client or server may include a cache, though a cache cannot be used by a server while it is acting as a tunnel.

Any given program may be capable of being both a client and a server; our use of these terms refers only to the role being performed by the

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.