

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/056022 A2

(51) International Patent Classification⁷: **H04J**
(21) International Application Number:
PCT/KR2003/001083
(22) International Filing Date: 2 June 2003 (02.06.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
10-2002-0079598
13 December 2002 (13.12.2002) KR

(71) Applicant (for all designated States except US): **ELECTRONICS AND TELECOMMUNICATIONS RESEARCH INSTITUTE** [KR/KR]; 161, Gajeong-dong, Yuseong-gu, Daejeon 305-350 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LEE, Sok-kyu** [KR/KR]; Jindalrae Apt. 105-1506, Wolpyung 3-dong, Seo-gu, Daejeon-city 302-754 (KR). **KIM, Kwang-Soon**

[KR/KR]; Hana Apt. 109-1203, Sinseong-dong, Yuseong-gu, Daejeon-city 305-721 (KR). **CHANG, Kyung-Hi** [KR/KR]; Clover Apt. 104-1409, Dun-san-dong, Seo-gu, Daejeon-city 302-772 (KR).


(74) Agent: **YOU ME PATENT AND LAW FIRM**; Teheran Bldg., 825-33, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR SIGNAL CONSTITUTION FOR DOWNLINK OF OFDMA-BASED CELLULAR SYSTEM



(57) Abstract: Disclosed are an adaptive pilot symbol assignment method that flexibly controls the number of transmit antennas according to each user's moving speed, channel status, or user request, and assigns proper pilot symbols in the downlink of an OFDMA (Orthogonal Frequency Division Multiplexing Access) based cellular system; and a sub-carrier allocation method for high-speed mobile that allocates some sub-carriers to assign proper pilot symbols for ultrahigh-speed mobile users, and the rest of the sub-carriers to the other users to assign proper pilot symbols to the users, on the assumption that the ultrahigh-speed mobile users have a traffic volume almost insignificant to the whole traffic volume.

WO 2004/056022 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

APPARATUS AND METHOD FOR SIGNAL CONSTITUTION FOR DOWNLINK OF OFDMA-BASED CELLULAR SYSTEM

5

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention relates to an apparatus and method for signal constitution for a downlink of an OFDMA (Orthogonal Frequency Division Multiplexing Access) based cellular system. More specifically, the present invention relates to an apparatus and method for adaptive pilot symbol assignment and sub-carrier allocation that reduces transmission power consumption and overhead caused by pilot symbols and increases the total data rate on the downlink of an OFDMA-based cellular system.

(b) Description of the Related Art

15 In the design of pilot assignment, it is necessary to use a sufficiently large number of pilot symbols for the sake of preventing a deterioration of reception performance caused by a channel variation, and to prevent an excessive increase of a power loss or a bandwidth loss caused by pilot symbols above an expected value. The positioning (assignment) of pilot symbols is of a great significance to the receiver of an OFDMA-based system, which estimates a transfer function value of channels in a two-dimensional (time, frequency) space. Hence, both the time domain and the frequency domain must be taken into consideration in pilot symbol assignment so as to transmit the pilot symbols. In case of using a plurality of antennas, the pilot symbols of the multiple antennas are assigned in

20

25

consideration of both the time domain and the frequency domain.

The distance between pilot symbols must be quite small in designing pilot symbols in the worst environment, or when using non-optimal channel estimation filters having a lower complexity.

5 Let f_{sc} be a sub-carrier bandwidth, then the maximum pilot distance N_F in the frequency domain based on the conventional sampling theory (F. Classen, M. Speth, and H. Meyr, "Channel estimation units for an OFDM system suitable for mobile communication", in ITG Conference on Mobile Radio, Neu-Ulm, Germany, Sept. 1995) is determined by the following
10 formula:

[Formula 1]

$$N_F \leq \frac{1}{\tau_{\max} f_{sc}}$$

where τ_{\max} is the maximum exceedance delay time of a channel. The maximum pilot distance N_T in the frequency domain is determined by the
15 following formula:

[Formula 2]

$$N_T \leq \frac{1}{2f_D T_s}$$

where f_D is the maximum Doppler frequency; and T_s is the symbol time.

The symbol time T_s , during which the maximum pilot distance is
20 proportional to the coherent time, is normalized by the number of symbols. So, the maximum pilot distance in the time domain is proportional to the coherent bandwidth and normalized by the sub-carrier bandwidth.

The balanced design (P. Hoeher et al., "Pilot-symbol-aided channel estimation in time and frequency", Multi-carrier Spread-Spectrum, accepted for publication in *Kluwer Academic Publishers*, 1997) defines that the estimation uncertainty in the time domain is equal to that in the frequency domain. Here, P. Hoeher et al. suggest a design guide having two-fold oversampling as defined by a heuristic formula as follows:

[Formula 3]

$$2f_D T_s \cdot N_T \approx \tau_{\max} f_{sc} \cdot N_F \approx \frac{1}{2}$$

where N_F is the pilot distance in the frequency domain. The above-mentioned pilot symbol assignment is primarily a rectangular pilot symbol assignment, which is illustrated in FIG. 1. FIGS. 2 and 3 show a straight pilot symbol assignment and a hexagonal pilot symbol assignment, respectively. Generally, the hexagonal pilot symbol assignment allows more efficient sampling, compared with two-dimensional signals, and exhibits excellent performance relative to other assignments. An example of the pilot symbol assignment is disclosed in "Efficient pilot patterns for channel estimation in OFDM systems over HF channels" (M. J. Fernandez-Getino Garcia et al., in *Proc IEEE VTC1999*).

As the pilot symbol assignment becomes denser, the channel estimation performance becomes more excellent but the data rate is decreased. Hence, a trade-off lies between the data rate and the channel estimation performance (i.e., pilot symbol distance).

There exists a pilot symbol distance that optimizes the trade-off

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.