



US 20050075125A1

(19) **United States**

(12) **Patent Application Publication**
Bada et al.

(10) **Pub. No.: US 2005/0075125 A1**

(43) **Pub. Date: Apr. 7, 2005**

(54) **METHOD AND MOBILE STATION TO PERFORM THE INITIAL CELL SEARCH IN TIME SLOTTED SYSTEMS**

(76) Inventors: **Anna Marina Bada, Milano (IT); Chiara Cavaliere, Rho (IT)**

Correspondence Address:
**BIRCH STEWART KOLASCH & BIRCH
PO BOX 747
FALLS CHURCH, VA 22040-0747 (US)**

(21) Appl. No.: **10/498,521**

(22) PCT Filed: **Jan. 21, 2002**

(86) PCT No.: **PCT/IT02/00035**

Publication Classification

(51) **Int. Cl.⁷ H04Q 7/20**


(52) **U.S. Cl. 455/525**

(57) **ABSTRACT**

A method is disclosed that a Mobile Station MS performs at switch-on to search the most favorable target cell in UMTS systems like the 3GPP CDMA—LCR (Low Chip Rate) option at 1.28 Mcps—TDD (Time Division Duplex) mode and the equivalent TD-SCDMA (Time Division—Synchronous CDMA). Signal at the MS antenna is the sum of different RF downlink frames coming from different carriers in the assigned frequency ranges. A DL synchronization timeslot and a BCCH TS0 are both transmitted with full power in the frames, the first one includes one out of 32

SYNC codes assigned on cell basis. Following a conventional approach the absence of a common downlink pilot and without prior knowledge of the used frequencies would force the MS, for all the frequencies of the channel raster stored in the SIM card, the correlation of the received frame with all the 32 SYNCs stored in the MS, in order to detect the BSIC of a cell to which associate the power measures. Following the two-step method of the invention the power measures are performed in two-step scan of the PLMN band without interleaved correlation steps; once a final frequency is selected the respective frame is the only correlated one. At least one frame duration about 5 ms long of the whole 15 MHz bandwidth is acquired, IF converted, A/D converted and the digital set is stored. A rough scan is performed multiplying the digital set by a digital IF tuned in steps wide as the channel band (1.6 MHz) along the 15 MHz band, and filtering the baseband signal with a Root Raise Cosine low-pass filter. The 5 ms baseband signal is subdivided into 15 blocks of half timeslot (337.5 μs) and the power of each block is measured. The power of the strongest block indicates the priority of the respective frequency. The strongest power values are put in a Spectral Table together with respective frame load indicators. The load indicator is the percentage of timeslots in a frame almost equally loaded as the strongest block. The three strongest frequencies are selected for the successive scan. The second step search is performed like the first one but the IF steps are now 200 kHz wide and cover the only 1.6 MHz spectrum around a selected frequency. A final frequency is selected for the successive correlation step. Then the frequency error of the MS reference oscillator is corrected with data-aided techniques and a calibration value stored for successive connections (FIG. 9).

POSSIBLE SIMPLIFIED RF SCENARIO



POSSIBLE SIMPLIFIED RF SCENARIO

 = CDMA FREQUENCY SUBSET (PLMN1)
 = GSM FREQUENCY SUBSET (PLMN2)




Fig. 1

KNOWN ART

GSM (or DCS) DOWNLINK SYNCHRONIZATION MULTIFRAME




Fig. 2a

GSM (or DCS) FREQUENCY CORRECTION AND SYNCHRONIZATION BURSTS




Fig. 2b

ULTRA-FDD (W-CDMA): RADIO FRAME STRUCTURE OF THE SYNCHRONIZATION CHANNEL SCH (KNOWN ART)




Fig. 3

UTRA-TDD (3.84 Mcps): RADIO FRAME STRUCTURE OF THE SYNCHRONIZATION CHANNEL SCH (KNOWN ART)




Fig. 4

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.